



DECLARATION OF PERFORMANCE

DoP [EN] No. 057 DURO-CPR-7-2013

1. Unique identification code of product-type:
ROMIX THERMO
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The coding shown on the packaging is the production date of the product.
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
General purpose rendering mortar for internal and external use GP: CSIV/W2.
4. Name, register name or register trade mark and contact address for the manufacturer as required to Article 11:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE
5. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4.
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 998-1: 2010
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
9. Declared performance:

Essential characteristics	Declared performance	Harmonized Technical specification
Reaction to fire	Euroclass A1	
Compression strength	CSIV $\geq 6.0\text{N/mm}^2$	EN 1015-11
Capillary water absorption	$W_2 < 0.20\text{kg/m}^2 \cdot \text{min}^{0.5}$	EN 1015-18
Adhesion to concrete	$\geq 1.0\text{N/mm}^2$	EN 1015-12
Water vapour permeability	$\mu = 15/35$	EN 1015-21
Thermal conductivity $\lambda_{10, \text{dry}}$ P=50%	0.82	EN 1745: 2000

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Evdoxia Kafritsa

Aspropyrgos 11/07/2013

R&D Manager, QC mortars lab



DUROSTICK S.A

ASPROPYRGOS ATHENS PC: 19300

GREECE

13

EN 998-1:2010

ROMIX THERMO

DoP No. : 057

General purpose rendering

Internal-External use

GP: CSIV/W2

Reaction to fire : Euroclass A1

Adhesion: > 1N/mm² - FP: B

Water absorption: W2

Water vapour diffusion coef.: μ 15/35

Thermal conductivity ($\lambda_{10,dry}$): 0.82 (Tab. Mean value; P=50%)

Durability: (against freeze/thaw): evaluation based on provisions valid in the intended place of use of the mortar

