



DECLARATION OF PERFORMANCE

DoP [EN] No. 029.DURO-CPR-7-2013

1. Unique identification code of product-type:
DSUROSTICK D-1.
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The coding shown on the packaging is the production date of the product.
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
Product for surface protection of concrete surfaces (c).
4. Name, register name or register trade mark and contact address for the manufacturer as required to Article 11:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE
5. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4.
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 1504 - 2.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
9. Declared performance:

Essential characteristics	Declared performance	Harmonized Technical specification
Permeability S_D to CO ₂	Complies	EN 1062-6 (Method A)
Water vapour permeability	Complies	EN ISO 7783-2
Capillary water absorption	Complies	EN 1062-6
Adhesion to concrete	Complies	EN 1542
Fire resistance	Euroclass A1	
Dangerous substances	Complies (see MSDS)	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Evdoxia Kafritsa

Aspropyrgos 10/07/2013

R&D Manager, QC mortars lab



**DUROSTICK S.A
ASPROPYRGOS ATHENS PC: 19300
GREECE
12**

EN 1504-2

**DUROSTICK D-1
DoP No. : 29**

Surface protection product - Coating

Permeability to CO₂:	S_d >50m
Water vapour permeability:	Class I (permeable)
Capillary absorption:	w ≤ 0.1 kg·m⁻²·h^{-0.5}
Adhesive strength:	≥ 1.0 N/mm²
Reaction to fire:	Euroclass F
Dangerous substances:	Comply with 5.4