



DECLARATION OF PERFORMANCE

DoP [EN] No. 053 DURO-CPR-7-2013

1. Unique identification code of product-type:
DUROSTICK D-11
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The coding shown on the packaging is the production date of the product.
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
Fast setting repair mortar.
4. Name, register name or register trade mark and contact address for the manufacturer as required to Article 11:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE
5. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4.
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 1504 - 3
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
9. Declared performance:

Essential characteristics	Declared performance	Harmonized Technical specification
Reaction to fire	Euroclass A1	
Compressive strength	R2 class (≥ 15 MPa)	EN 12190
Chloride ion content	$\leq 0.05\%$	EN 1015-17
Capillary water absorption	$\leq 0.5 \text{ kg/m}^2\text{h}^{-0.5}$	EN 13057
Adhesive strength	$\geq 0.8 \text{ MPa}$	EN 1542
Adhesive strength after freeze-thaw cycles	$\geq 0.8 \text{ MPa}$	EN 13687-1
Dangerous substances	Complies (see MSDS)	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Evdoxia Kafritsa



DUROSTICK S.A
ASPROPYRGOS ATHENS PC: 19300
GREECE
12

EN 1504-3

DUROSTICK D-11
DoP No. : 053

**Concrete repair product for non structural repair
PCC mortar (based on hydraulic cement, polymer
modified)**

Compressive strength:	class R2
Chloride ion content:	≤ 0.05%
Adhesive strength:	≥ 0.8 MPa
Thermal compatibility part 1:	≥ 0.8 MPa
Capillary absorption:	≤ 0.5 kg/m².h^{-0.5}
Dangerous substances:	comply with 5.4
Reaction to fire:	Euroclass A1