



DECLARATION OF PERFORMANCE

DoP [EN] No. 099.DURO-CPR-9-2014

1. Unique identification code of product-type:
DUROSTICK DUROSIL FIRE
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The six-digit number printed on the package corresponds to the Batch Production Number of product.
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
Sealant for internal and external facade elements: EN 15651 - 1: F - EXT - INT - CC, Sealant for glazing applications: EN 15651 - 2: G - CC.
4. Name, register name or register trade mark and contact address for the manufacturer as required to Article 11:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE.
5. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 15651 - 1, EN 15651 - 2.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
9. Declared performance:
Preparation: PROCEDURE A (IN ACCORDANCE WITH ISO 8340)
Substrate: GLASS (without primer) and Aluminium (without primer)

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	Class E	
Release of Chemicals	None	See product safety data sheet
Water Tightness & Air Tightness as determined by :		
Resistance to flow	≤3mm	EN15651-1,2
Loss of volume	≤10%	EN15651-1,2
Adhesion/Cohesion at maintained extension after immersion in water	No Failure	EN15651-1
Adhesion/Cohesion at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	No Failure	EN15651-1,2

Adhesion/Cohesion properties after exposure to heat water and artificial light	Pass Glass	EN15651-2
Elastic recovery	≥60%	EN15651-2
Durability	Pass	EN15651-1,2

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Dr. Aristides Koutsibelis

Aspropyrgos 22/09/2014

R&D Manager, QA fluids lab



DUROSTICK S.A
ASPROPYRGOS ATHENS PC: 19300
GREECE
14

EN 15651-1: F-EXT-INT-CC
EN 15651-2: G-CC

DUROSIL FIRE

DoP No. : 99

Reaction to fire:	Class E
Release of Chemicals:	None
Water Tightness & Air Tightness as determined by :	
Resistance to flow:	≤3mm
Loss of volume:	≤10%
Adhesion/Cohesion at maintained extension after immersion in water:	No Failure
Adhesion/Cohesion at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C):	No Failure
Adhesion/Cohesion properties after exposure to heat water and artificial light:	Pass Glass
Elastic recovery:	≥ %60
Durability:	Pass