

# DUROSTICK D-29 SPOT FREE

Oil repelling and waterproofing impregnating agent for tile & granite

## PROPERTIES

Siloxane based, oil repellent and waterproofing liquid, with high penetrating ability (micro technology). Once dry, the product creates an invisible and protective surface film, which does not peel and does not slip, even when the surface gets wet. Prevents stains from oils, wine and soft drinks, ink, as well as the creation of pet stains. Stains from mudrain and air pollutants are easily removed from surfaces protected with D-29 SPOT FREE.

## APPLICATIONS

DUROSTICK D-29 SPOT FREE is the necessary waterproofing agent for **non** absorbent and/or **non** glazed tiles, matte and shiny granite, natural cotto, both indoors and out. Apply DUROSTICK D-29 SPOT FREE on kitchen countertops made of marble or granite, to keep them stain free. When installing absorbent tiles, granite and cotto, it is recommended to use the product before grouting with dark color grouting materials.

By so doing, the risk of the surface discoloration or staining, from the strong pigments of the grouting materials, is avoided and the cleaning process is facilitated at the same time.

## USE

### 1. Surface preparation

Three weeks after completing the tile installation and the grout is thoroughly dry, clean all construction residues using DUROSTICK ACID CLEANER. When dealing with existing tiles, refresh and clean the surface using the biodegradable grout cleaner for tile and granite, DUROSTICK BIOCLEAN.

### 2. Application

Apply DUROSTICK D-29 SPOT FREE undiluted, using a paint roller or a brush (pic.1,2), on dust free and dry surfaces. When dealing with an absorbent surface and the first coat is immediately absorbed, it is recommended to apply a second coat while the first one is still wet. Remove all residues with a dry, soft, lint-free cloth.



pic. 1



pic. 2

## TECHNICAL SPECIFICATIONS

Form - Color	Liquid - Transparent
Density	0.77 ± 0.04 kg/lt
Gloss	Matte
Application temperature	From +5°C to +35°C
Foot traffic	After 12 hours
Duration of watertightness	2 years (exterior waterproofing) 5 years (interior waterproofing)
Water absorption coefficient	W ≤ 0.5 kg/m <sup>2</sup> ·h

### VOC (Volatile Organic Compounds):

Limit value of maximum V.O.C. content according to EC (Directive 2004/42/EC) for the particular product (class A/h 'Binding primers', Type SB): 750 gr/lt (2010). Ready to use product contains maximum 672 gr/lt V.O.C.

## CONSUMPTION

100-150ml/m<sup>2</sup> per coat.

## STORAGE

Store in shaded places away from any heat source, for at least 18 months after production date.

## SAFETY DIRECTIONS

The product is classified as harmful. It is recommended to keep away from the reach of children and apply in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

## NOTE

After drying, the product is harmless to health and the environment.

## PACKAGING

Carton box with 15 pcs. of 1lt each one  
Carton box with 6 pcs. of 4lt each one