DUROSTICK ADHESIVE FOR FOAM INSULATION PIPES

PROPERTIES
Powerful neoprene and synthetic resin adhesive.

It provides powerful adhesion and flexible bonding to foam insulation materials, so as to withstand temperature variations, where it is applied. The container cap has a built-in round brush for easy applications (pic.2)

APPLICATIONS
Existing piping systems exposed to frost (solar water heater pipes) should be protected with foam insulation. Exposed metal or PVC piping for gardens or hot water pipes must be protected from the elements with foam insulation as well. Ensure their installation using DUROSTICK

ADHESIVE FOR FOAM INSULATION safeguards all piping systems from adverse weather/ambient conditions.

USE
1. Surface preparation
Using a razor blade, slice one side of the foam insulation. Split open with your fingers and wrap around the pipes to protect them.

2. Application
Before use, shake the container well and apply a thin layer of adhesive on both sides of the foam insulation (pic.1,2). Allow for the adhesive to set for 10 minutes and then press the two sides together to join them. Close the container well after use.

TECHNICAL SPECIFICATIONS

Form - Color	Thixotropic liquid - Honey
Density	0.80 ± 0.04 kg/lt
Application temperature	From +5˚C to +35˚C
Temperature resistance	From -20˚C to +70˚C

CONSUMPTION
Depending on the application.

STORAGE
Store in tightly closed containers, in shaded places, away from any heat source, for at least 18 months from production date.

SAFETY DIRECTIONS
The product is classified as highly flammable and harmful. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

NOTE
After drying, the product is harmless to health.

PACKAGING
Carton box with 12 pcs. of 200ml each one

pic. 1

pic. 2