

6.5 Emulsion paints for plaster & concrete

ROMIX TRADE SERIES General purpose emulsion paint

PROPERTIES

Trade series waterborne emulsion paint based on PVA-VEOVA copolymers.

It provides bright white finishes, high coverage and maintains the breathability of the applicable surfaces.

Its formula requires but a minimum quantity of pigments for the creation of the desired color. It is the affordable choice for renewing all indoor surfaces.

APPLICATIONS

ROMIX TRADE SERIES is suitable for existing or new indoor surfaces made of plaster, drywall, MDF on walls, ceilings, staircases and hallways etc.

USE

1. Substrate preparation

Surfaces from marble based plaster have to be dry, at least 30 days from their construction, and free from loose materials.

For new marble based plaster surfaces, sand them down using #60 sandpaper and prime using PVA PRIMER, 100% ACRYLIC PRIMER or AQUAFIX, the micromolar stabilizer of DUROSTICK.

For skimming or spackling, use STUCOFIX putty, STUCOFIX-P, POWDER COAT, GRANULAR ULTRA or GRANULAR of DUROSTICK, or any combination of the above, depending

on the surface imperfections and smoothness of the finish required. Follow by priming the surfaces.

Already painted surfaces require just two coats of ROMIX TRADE SERIES.

Surfaces soiled with soot and air pollution, are cleaned with the biodegradable cleaner BIOCLEAN (for nicotine and soot) or they are primed with METAL PRIMER of DUROSTICK.

For peeling surfaces, remove all loose materials and prime using 100% ACRYLIC PRIMER, or AQUAFIX, micromolar stabilizer of DUROSTICK.

Marble based plaster surfaces with severe cracks, are sealed with fast setting repair plaster D-32. Prime the sealed surfaces.

Fill the joints around door and window casings, by using the paintable ACRYLIC CAULK for interior use, or the versatile sealant and adhesive DS-POLYMER, available in 32 colors.

2. Application

Dilute ROMIX TRADE SERIES with water at a ratio of up to 5%, depending on the substrate, and mix well.

Apply with brush, roller or airless spray gun in 3 coats.

Apply each additional coat, after the previous one is completely dry.

CLEANING

Clean all tools with water and detergent solution, immediately after use.



TECHNICAL SPECIFICATIONS

Available color	White that does not yellow over time
Colors	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors.
Washability	> 5.000 cycles (per DIN 53778)
Gloss	Matte
Drying time	1 hour (touch dry), depending on the ambient conditions
Recoating time	4-5 hours, depending on the ambient conditions
Application temperature	From +8°C to +35°C
Flammable	No

V.O.C. (Volatile Organic Compounds):

Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/a: 'Matte coatings for interior walls and ceilings' Type WB): 30gr/lit (2010). Ready to use product contains maximum 21gr/lit V.O.C.



CONSUMPTION

1kg/5-6m² per coat, on properly prepared surfaces.

STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date.

NOTE

If needed, it is recommended to clean the freshly painted surface that ROMIX TRADE SERIES was used, with a soft sponge and mild detergent, 30 days after its application.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs of 1kg (750ml) each one
5kg (3lt) container (on a 120pc pallet)
15kg (9lt) container (on a 48pc pallet)