

DUROSTICK WOOD CLEANER Cleaner for woodwork and garden furniture

PROPERTIES

Powerful cleaning liquid with active ingredients. The product presents excellent penetrating ability in hard or soft wood pores. Use it to remove difficult, accumulated stains such as oils, salts, gray and black spots etc. Ready to use and easy to apply, it restores wood to their natural color without destroying them.

APPLICATIONS

DUROSTICK WOOD CLEANER is a highly effective cleaning liquid for exterior wood surfaces and constructs, garden (pic. 2) and terrace furniture (tables, chairs, benches etc.), as well as pergolas, wood patios and pool decks, pleasure boat decks (pic. 1) and other wood surfaces (existing doors and windows) to be cleaned. Protect the now clean surfaces using TEAK OIL of DUROSTICK or any one of the DUROSTICK wood varnishes. The product can also be used at regular intervals for the maintenance of any uncoated, bare wood surface.

USE

- Shake well before use.
- Soak the surface, spray the cleaning liquid and allow for it to act for 2 to 5 minutes.
- Using a cleaning sponge or a stiff broom (suitable for floor and deck cleaning), scrub the surface evenly, following the wood grain.
- Rinse with water during and immediately after the cleaning. process. For

severely weathered and heavily soiled surfaces, repeat the process.

- Allow for the clean surface to dry for, at least 24 hours before applying TEAK OIL or any other protective varnish(*).

(*DUROSTICK highly recommends that after cleaning with WOOD CLEANER, and all surfaces have dried thoroughly, protect them using the clear impregnation preservative DUROXYL WOOD Protection / Conditioner to protect the woodwork (doors, windows, pergolas, balusters, fences, balconies, terraces, etc.). For additional protection of all outdoor surfaces, especially against intense sunshine, it is highly recommended to apply either DUROLAC (available in satin or gloss finish) or MARINER (gloss finish) varnishes of DUROSTICK.

NOTES

- Old varnishes or enamel paints are removed using DUROSTICK D-26 corrosive and remover for paints and varnishes, before applying WOOD CLEANER.
- Avoid any contact of WOOD CLEANER with paints, various metal surfaces, fiberglass and aluminum.
- During the application and the rinse steps it is recommended to wear protective gloves.
- Make sure the product's residues do not accumulate near plants to avoid damaging them.



TECHNICAL SPECIFICATIONS

Form - Color	Liquid - Transparent
Density	1.05 ± 0.05 kg/l
pH	13,0 ± 0,50
Application temperature	From +5°C to +35°C
Application method	Sponge, stiff broom
Dilution	The product is ready for use. Do not dilute.
Flammable	No
Contains sodium hydroxide and, among others, anionic, amphoteric surfactants of less than 5% and phosphonates less than 5%	

Permit No. by General Chemical State Laboratory ELEFSIS 3093/2008

CONSUMPTION

1lt/6-10m², depending on the absorbency and type of the surface of the wood.

STORAGE

Store in shaded places, for at least 36 months from production date.

SAFETY DIRECTIONS

The product is classified as corrosive. It is recommended to keep away from the reach of children and apply in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 12 pcs. of 500ml each one
Carton box with 12 pcs of 1.2lt each one



pic. 2



pic. 1