

ULTRALIGHT PUTTY



Lightweight repair acrylic putty



■ PROPERTIES

Lightweight, odorless, repair acrylic putty, with zero shrinkage.

■ ADVANTAGES

- Ready to use and easy to work with
- Maximum filling capacity with minimal weight
- Does not burst nor crack
- Strongly adheres to any building surface, painted or not, creating a smooth surface
- Does not require sanding
- Quick drying, can be drilled and nailed
- Paintable over in less than an hour, without primer.

■ APPLICATIONS

ULTRALIGHT PUTTY of DUROSTICK is suitable for quick crack repairs and the patching of holes, up to

5cm deep. Use it on walls, ceilings, and plastered surfaces made of concrete, wood, and drywall, both indoors and out. Apply a single coat to cover capillary cracks.

■ USE

1. Surface preparation

Cracks have to be cleaned and possible loose materials have to be removed. All surfaces have to be free from dust, lime and oils. Lightly soak the surface before application.

2. Application

Apply it on new or existing, already painted surfaces. Use a damp plastic or metal putty knife, at ambient temperatures ranging from +5°C to +35°C. Touch dry in about 30-60 minutes. Paintable in less than an

ULTRALIGHT PUTTY



Lightweight repair acrylic putty

hour, always depending on the application thickness and the ambient conditions (temperature - humidity).

■ NOTE

When applied in very small thicknesses to cover hairline cracks, it does not create a visible patch nor does it leave any blemishes, due to the fact that it turns almost transparent when dry.

■ CLEANING

Clean all tools with water, immediately after use.

■ CONSUMPTION

Depending on the application.

■ STORAGE

Store in the factory sealed packaging, in places protected from frost, for 18 months from production date.

TECHNICAL SPECIFICATIONS	
■ Form - Color	Putty - White
■ Density	0.36±0.03kg/lt
■ Application temperature	From +5°C to +35°C
■ Painting	After 30-60 minutes, depending on the application thickness.

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.