

DECLARATION OF PERFORMANCE

No. 163

1. Unique identification code of the product-type: **TECHNOPROOF THERMO**
2. Intended use/es: **Surface protection products-coating-ingress protection (1.3)-moisture control (2.2) increasing resistivity (8.2)**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr
4. Authorised Representative: -
5. System/s of AVCP: **System 4**
6. Harmonised standard: **EN 1504-2:2004**
7. Declared performance/s:

Essential Characteristics	Performance
Permeability to CO ₂	S _D > 50 m
Permeability to water vapour	Class I, S _D < 5 m
Capillary absorption and permeability to water	w < 0.1 kg/m ² · h ^{0,5}
Adhesion strenght by pull off test	≥ 0.8 N/mm ²
Reaction to fire	Euroclass F
Dangerous substances	Comply with 5.3

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Aristides Koutsibelis - Dr Chemist
Manager Research & Quality Assurance



Aspropyrgos 08/09/2023

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

22

DoP No. : 163

EN 1504-2:2004

TECHNOPROOF THERMO

Surface protection products
Coating

Permeability to CO ₂	$S_D > 50 \text{ m}$
Permeability to water vapour	Class I, $S_D < 5 \text{ m}$
Capillary absorption and permeability to water	$w < 0.1 \text{ kg} / \text{m}^2 \cdot \text{h}^{0,5}$
Adhesion strenght by pull off test	$\geq 0.8 \text{ N/mm}^2$
Artificial weathering	Pass
Reaction to fire	Euroclass F
Dangerous substances	Comply with 5.3