

DECLARATION OF PERFORMANCE

No. 004

1. Unique identification code of the product-type: **PROFESSIONAL**
2. Intended use/es: **Improved cementitious adhesive with extended open time**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: **Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr**
4. Authorised Representative:
5. System/s of AVCP: **System 3**
6. Harmonised standard: **EN12004:2007+A1:2012**
Notified Body: **MIRTEC S.A. No. 0437**
7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Bond strength as: Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
Durability for: Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$
Release of dangerous substances	See SDS


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Zoi Athanasiou - Head of Mortar Lab



Aspropyrgos 11.09.2023

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

07

DoP No. : 004

EN12004:2007+A1:2012

PROFESSIONAL

Improved cementitious adhesive with extended open time,
for internal and external tiling

Reaction to fire	Class A1
Release of dangerous substances	See SDS
Bond strength as:	
Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
Durability for:	
Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$