

**DECLARATION OF PERFORMANCE**

No. 015

1. Unique identification code of the product-type: **D-65**
2. Intended use/es: **Cementitious screed material for use internally in buildings**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**  
**Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr**
4. Authorised Representative:
5. System/s of AVCP: **System 4**
6. Harmonised standard: **EN13813:2002**
7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Release of corrosive substances	CT
Water permeability	NPD
Water vapour permeability	NPD
Compressive strength	C30
Flexural strength	F6
Wear resistance	AR2
Sound insulation	NPD
Sound absorption	NPD
Thermal resistance	NPD
Chemical resistance	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

**Zoi Athanasiou - Head of Mortar Lab**



Aspropyrgos **31.07.2023**

CE MARKING



**DUROSTICK S.A.**  
ASPROPYRGOS-ATHENS PC: 19300  
GREECE

09  
DoP No. : 015

EN13813:2002

**D-65**

Cementitious screed material for use internally in buildings

Reaction to fire	Class A1
Release of corrosive substances	CT
Water permeability	NPD
Water vapour permeability	NPD
Compressive strength	C30
Flexural strength	F6
Wear resistance	AR2
Sound insulation	NPD
Sound absorption	NPD
Thermal resistance	NPD
Chemical resistance	NPD