

**DECLARATION OF PERFORMANCE**

No. 053

1. Unique identification code of the product-type: **D-11 SUPER FAST**
2. Intended use/es: **Repair mortar PCC for non structural repair of concrete structures.**  
Class R2. Principles 3 (CR) & 7 (RP) according to EN 1504-9:2008
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**  
Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, [www.durostick.gr](http://www.durostick.gr)
4. Authorised Representative:
5. System/s of AVCP: **System 4**
6. Harmonised standard: **EN 1504-3:2005**

7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Compressive strength	Class R2
Chloride ion content	≤ 0.05%
Adhesive bond	≥ 0.8 Mpa
Thermal compatibility part 1 (freeze-thaw)	≥ 0.8Mpa
Capillary absorption	≤ 0.5 kg · m <sup>-2</sup> · h <sup>-0.5</sup>
Dangerous substances	Comply with 5.4


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
**Zoi Athanasiou - Head of Mortar Lab**



Aspropyrgos 01.06.2023

CE MARKING



**DUROSTICK S.A.**  
ASPROPYRGOS-ATHENS PC: 19300  
GREECE

12  
DoP No. : 053

EN 1504-3:2005

**D-11 SUPER FAST**

Concrete repair product for non structural repair PCC mortar  
(based on hydraulic cement, polymer modified)

Compressive strength	Class R2
Chloride ion content	≤ 0.05%
Adhesive bond	≥ 0.8 Mpa
Thermal compatibility part 1	≥ 0.8 Mpa
Capillary absorption	≤ 0.5 kg· m <sup>-2</sup> · h <sup>-0,5</sup>
Dangerous substances	Comply with 5.4
Reaction to fire	Class A1