

**DECLARATION OF PERFORMANCE**

No. 060

1. Unique identification code of the product-type: **D-40**
2. Intended use/es: **General purpose rendering / plastering mortar (GP)**  
For external and internal use
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**  
Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, [www.durostick.gr](http://www.durostick.gr)
4. Authorised Representative:
5. System/s of AVCP: **System 4**
6. Harmonised standard: **EN 998-1:2016**

7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Water absorption	W <sub>c</sub> 1
Water vapour diffusion coeff.	μ 15/35
Adhesion	≥ 0.50 N/mm <sup>2</sup> - FP: B
Thermal conductivity (λ <sub>10,dry</sub> )	1.11 W/m · K (tab. value)
Durability (against freeze-thaw)	NPD
Dangerous substances	See SDS


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
**Zoi Athanasiou - Head of Mortar Lab**



Aspropyrgos 13.09.2023

CE MARKING



**DUROSTICK S.A.**  
ASPROPYRGOS-ATHENS PC: 19300  
GREECE

07

DoP No. : 060

EN 998-1:2016

**D-40**

General purpose rendering / plastering mortar (GP)  
for external and internal use

Reaction to fire	Class A1
Water absorption	W <sub>c</sub> 1
Water vapour diffusion coeff.	μ 15/35
Adhesion	≥ 0.50 N/mm <sup>2</sup> - FP: B
Thermal conductivity (λ <sub>10,dry</sub> )	1.11 W/m·K (tab. value)
Durability (against freeze-thaw)	NPD
Dangerous substances	See SDS