

DECLARATION OF PERFORMANCE

No. 062

1. Unique identification code of the product-type: **D-42 ONE COAT**
2. Intended use/es: **One coat rendering mortar (OC)**
For external use
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr
4. Authorised Representative:
5. System/s of AVCP: **System 4**
6. Harmonised standard: **EN 998-1:2016**
7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Water absorption	W _c 1
Water permeability after weathering cycles	≤ 1 ml/m ²
Water vapour diffusion coeff.	μ 15/35
Adhesion after weathering cycles	≥ 0.40 N/mm ² - FP: B
Thermal conductivity (λ _{10,dry})	0.82 W/m · K (tab. value)
Durability (against freeze-thaw)	NPD
Dangerous substances	See SDS


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Zoi Athanasiou - Head of Mortar Lab



Aspropyrgos 20.07.2023

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

10
DoP No. : 062

EN 998-1:2016

D-42 ONE COAT

One coat rendering mortar
for external use

Reaction to fire	Class A1
Water absorption	Wc1
Water permeability after weathering cycles	$\leq 1 \text{ ml/m}^2$
Water vapour diffusion coeff.	$\mu 15/35$
Adhesion after weathering cycles	$\geq 0.40 \text{ N/mm}^2$ - FP: B
Thermal conductivity ($\lambda_{10,\text{dry}}$)	0.82 W/m·K (tab. value)
Durability (against freeze-thaw)	NPD
Dangerous substances	See SDS