

DECLARATION OF PERFORMANCE

No. 079

1. Unique identification code of the product-type: **VINYL 500 EXTRA FLEX**
2. Intended use/es: **Improved highly deformable cementitious adhesive with reduced slip and extended open time**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr
4. Authorised Representative:
5. System/s of AVCP: **System 3**
6. Harmonised standard: **EN12004:2007+A1:2012**
- Notified Body: **ZÚS No. 1020**
ITC DIVIZE CSI No. 1390

7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Bond strenght as: Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
Durability for: Tensile adhesion strength after heat ageing Tensile adhesion strength after water immersion Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$ $\geq 1.0 \text{ N/mm}^2$ $\geq 1.0 \text{ N/mm}^2$
Release of dangerous substances	See SDS


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Zoi Athanasiou - Head of Mortar Lab



Aspropyrgos 28.07.2023

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

07
DoP No. : 079

EN12004:2007+A1:2012

VINYL 500 EXTRA FLEX

Improved highly deformable cementitious adhesive with reduced slip and extended open time,
for internal and external tiling

Reaction to fire	Class A1
Release of dangerous substances	See SDS
Bond strenght as:	
Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
Durability for:	
Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$