



## DECLARATION OF PERFORMANCE

No. 083

1. Unique identification code of the product-type: **VINYL S200**
2. Intended use/es: **Improved cementitious adhesive with extended open time**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**  
**Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr**
4. Authorised Representative:
5. System/s of AVCP: **System 3**
6. Harmonised standard: **EN12004:2007+A1:2012**
- Notified Body: **MIRTEC S.A. No. 0437**

7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
<b>Bond strenght as:</b> Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
<b>Durability for:</b> Tensile adhesion strength after heat ageing Tensile adhesion strength after water immersion Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$ $\geq 1.0 \text{ N/mm}^2$ $\geq 1.0 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Zoi Athanasiou - Head of Mortar Lab**

Aspropyrgos 11.09.2023

## CE MARKING



**DUROSTICK S.A.**  
ASPROPYRGOS-ATHENS PC: 19300  
GREECE

07  
DoP No. : 083

EN12004:2007+A1:2012

### **VINYL S200**

Improved cementitious adhesive with extended open time,  
for internal and external tiling

<b>Reaction to fire</b>	Class A1
<b>Release of dangerous substances</b>	See SDS
<b>Bond strenght as:</b>	
Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$
<b>Durability for:</b>	
Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1.0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$