

DECLARATION OF PERFORMANCE

No. 028

1. Unique identification code of the product-type: **HYDROSTOP ROOF**
2. Intended use/es: **Surface protection product – Coating. Principle 1 (Ingress protection) – Method 1.3 / Principle 2 (Moisture control) – Method 2.3 / Principle 5 (Physical resistance) – Method 5.1 / Principle 8 (Increasing resistivity) – Method 8.3 according to EN 1504-9:2008**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr
4. Authorised Representative:
5. System/s of AVCP: **System 4**
- 6α. Harmonised standard: **EN 1504-2:2004**

7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class F
Abrasion resistance	Weight loss < 3000 mg
Permeability to CO ₂	S _D > 50 m
Permeability to water vapour	Class I, S _D < 5 m
Capillary absorption and permeability to water	w ≤ 0.1 kg/m ² · h ^{0.5}
Impact resistance	Class III
Adhesion strenght by pull off test	≥ 1.0 N/mm ²
Dangerous substances	Comply with 5.3


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Zoi Athanasiou - Head of Mortar Lab



Aspropyrgos 31.07.2023

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

12

DoP No. : 028

EN 1504-2:2004

HYDROSTOP ROOF

Surface protection product
Coating

Abrasion resistance	Weight loss < 3000 mg
Permeability to CO ₂	S _D > 50 m
Permeability to water vapour	Class I, S _D < 5 m
Capillary absorption and permeability to water	$w \leq 0.1 \text{ kg} / \text{m}^2 \cdot \text{h}^{0,5}$
Impact resistance	Class III
Adhesion strenght by pull off test	$\geq 1.0 \text{ N/mm}^2$
Reaction to fire	Class A1
Dangerous substances	Comply with 5.3