

DECLARATION OF PERFORMANCE

No. 110

1. Unique identification code of the product-type: **DS-258 DECO MICRO FLEX**
2. Intended use/es: **Surface protection products-coating-moisture control (2.2)-increasing resistivity (8.2)**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**
Production factory: Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr
4. Authorised Representative: **-**
5. System/s of AVCP: **System 4**
6. Harmonised standard: **EN 1504-2:2004**
7. Declared performance/s:

Essential Characteristics	Performance
Permeability to water vapour	Class I, $S_D < 5$ m
Capillary absorption and permeability to water	$w < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$
Adhesion strenght by pull off test	$\geq 1.0 \text{ N/mm}^2$
Reaction to fire	Euroclass F
Dangerous substances	Comply with 5.3


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
Aristides Koutsibelis - Dr Chemist
Manager Research & Quality Assurance



Aspropyrgos **30/10/2023**

CE MARKING



DUROSTICK S.A.
ASPROPYRGOS-ATHENS PC: 19300
GREECE

16

DoP No. : 110

EN 1504-2:2004

DS-258 DECO MICRO FLEX

Surface protection products
Coating

Permeability to water vapour	Class I, $S_D < 5$ m
Capillary absorption and permeability to water	$w < 0.1 \text{ kg} / \text{m}^2 \cdot \text{h}^{0.5}$
Adhesion strenght by pull off test	$\geq 1.0 \text{ N/mm}^2$
Reaction to fire	Euroclass F
Dangerous substances	Comply with 5.3