

# PVC PRIMER



For PVC pipes



## ■ PROPERTIES

PVC pipe and fitting cleaner.

It removes oils, fats, grease, and cuts through the pipe's surface glaze, leaving a rough surface. The PVC glue adheres more powerfully during the application process, offering an even stronger welding.

The container cap has a built-in round brush for easy applications.

## ■ APPLICATIONS

The necessity for a clean, to-be-welded, surface of PVC pipes and fittings, ensures a problem-free and meticulous project completion. This applies for both pressurized piping networks and for general applications.

Use the product to disassemble PVC pipes and fittings, after their saturation with PVC PRIMER, where necessary.

It is possible for the PVC GLUE to lose its workability, due to evaporation.

Restore its fluidity by mixing the required amount of PVC PRIMER and vigorously shake the container of the glue.

## ■ USE

### 1. Surface preparation

Using a dry cloth, remove any filth, soil or mud from the surfaces to be welded.

### 2. Application

Apply PVC PRIMER around the pipe or fitting surfaces, using the attached brush. Apply both internally and externally, to the points at which glue will later be applied.

The surfaces are ready for glue application and welding, when the primer dries.

## ■ CONSUMPTION

Depending on the diameter of the pipe and the necessity for cleaning it.

## ■ STORAGE

Store in tightly closed container, in shaded places, away from any heat source, for 24 months from production date.

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

# PVC PRIMER



---

## For PVC pipes

### ■ SAFETY DIRECTIONS

The product is classified as highly flammable and harmful. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

### ■ PACKAGING

Carton box with 12 pcs of 236ml each one.

TECHNICAL SPECIFICATIONS	
■ Form	Liquid
■ Color	Transparent
■ Density	0.85±0.05kg/lt
■ Application temperature	From +4°C to +35°C
■ Cleaning and thinning ability	Only for PVC pipes, fittings and PVC GLUE

**DUROSTICK S.A.,**  
MANUFACTURING OF ADHESIVES,  
PAINTS & MORTARS  
**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,  
Tel: +30 211 60 03 500-599, +30 210 55 16 500,  
+30 210 55 98 350, Fax: +30 210 55 99 612  
**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,  
STREET, DA 10, GR: 570 22,  
Tel: +30 2310 795 797, +30 2310 797 365,  
Fax: +30 2310 797 367  
Email: [info@durostick.com](mailto:info@durostick.com)

---

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.