

RED LEAD FOR PLUMBING



Elastomeric anticorrosive



■ PROPERTIES

Anticorrosive, elastomeric viscous liquid, for waterproofing metallic pipe threads.

It allows for the disassembly of fittings when needed. It prevents iron components from sticking together due to oxidation.

Provides corrosion protection and seals galvanized or not metallic pipe fittings when working together with plumbers' hemp.

The container cap has a built-in round brush for easy applications.

■ APPLICATIONS

Its long-term durability to hydraulic and machining facility applications ensures the operation of piping systems without future joint problems.

■ USE

1. Surface preparation

Remove any rust, fats, oils and grease from the threads.

2. Application

DUROSTICK RED LEAD FOR PLUMBING is ready for use. Apply an even coat and cover it with the required amount of plumber's hemp. Continue by covering with another coat. Screw the pipe or fitting

while the product is still fresh. If necessary, it can be diluted up to 10%, using DUROSTICK THINNER 101.

■ CONSUMPTION

Depending on the pipe diameter.

■ STORAGE

Store in tightly closed containers, in shaded places, away from any heat source, for 12 months from production date.

■ SAFETY DIRECTIONS

The product is classified as flammable and toxic. It is recommended to keep it locked, away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 12 pcs of 250gr each one.

RED LEAD FOR PLUMBING



Elastomeric anticorrosive

TECHNICAL SPECIFICATIONS	
■ Form - Color	Thixotropic paste - Orange
■ Density	1.62±0.08kg/lit
■ Application temperature	From +5°C to +40°C
■ Drying time	One hour (touch dry)
■ Curing	24 hours

V.O.C. (Volatile Organic Compounds)

Limit value of maximum content of V.O.C. per EU (Directive 2004/42/CE) for this product (category A/i: 'One-pack performance coatings', type SB): 500gr/lit (2010). The ready to use product contains maximum 450gr/lit V.O.C.

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.