

SEALANT



For foam insulation products



■ PROPERTIES

White acrylic elastomeric sealant, suitable for protecting foam insulation pipes. Distinguished for its ability to maintain the flexibility of the foam insulating pieces by preventing the sun from damaging (drying) them, leading to their gradual destruction. It contains powerful UV filters that prevent the bursting or peeling of the sealant.

■ APPLICATIONS

DUROSTICK SEALANT and paint for foam insulation, ensures the protection of all types of foam insulation. After their installation over exterior and interior copper, iron, PVC or polypropylene piping, use it to protect them from the weather elements and ageing. Ideal for the protection of foam insulation around solar water heaters and all kinds of plumbing systems.

It is necessary for the protection of new foam insulation to avoid their disintegration (often

occurrence). but also previously installed, but in good condition, foam insulation pieces.

Use it when drilling holes on the roof surface or walls to install various supports or equipment, to seal them before inserting the plastic or metallic anchors.

Available in white, can be colored using the Measuring System for Shade Rendering, DUROCOLOR of DUROSTICK (syringe packaging of 20ml each one), capable of creating 120 permanent colors.

■ USE

1. Surface preparation

All surfaces must be clean, dry and free from dust and loose materials.

2. Application

Stir the product and apply one to two coats, with a difference of 3-4 hours between coats.

SEALANT



For foam insulation products

■ LIMITATION OF USE

Do not apply if there is a chance of rain or frost for the next 12 hours.

■ CONSUMPTION

1.0-1.5kg/m² per coat.

■ STORAGE

Store in places protected from frost for 24 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation. However, it is recommended to keep away from the reach of children.

If swallowed, seek immediate medical advice and show the container or label.

■ NOTE

It prevents damage by the pecking of birds to the foam insulation. Its excellent adhesion to foam insulation makes it a more secure 'system', even from the coated foam insulation.

■ PACKAGING

Carton box with 12 pcs of 1kg each one.

TECHNICAL SPECIFICATIONS

■ Form - Color	Viscous liquid - White
■ Density	1.50±0.05kg/lit
■ Deformability (Per ASTM D412)	After curing for 8 days and to a membrane of 1mm thick, the elongation at break was found at 300%
■ Application temperature	From +8°C to +40°C
■ Temperature resistance	From -20°C to +80°C
■ Water tightness	7 atm per DIN 1048

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.