



## Crystal clear wood & paper glue



### ■ PROPERTIES

PVA-based, viscous glue, suitable for strong adhesions of wood and paper materials. Apply it easily using its container bottle with the controlled flow nozzle. It becomes clear when it dries and it offers easy and quick bonding solutions. Ideal for repairs, handicrafts, and various DIY constructions whether at school, at home, and/or at the office. It does not stain surfaces.

### ■ APPLICATIONS

DUROSTICK HOBBY strongly bonds wood, particle board, MDF, veneer, ceramics, paper, carton, modeling paper, wallpaper, polystyrene, cork, with each other and to other materials and/or surfaces.

### ■ USE

#### 1. Surface preparation

Clean all bonding surfaces from dust and loose materials.

#### 2. Application

Apply the undiluted glue uniformly on clean and dry surfaces. Allow for 5-10 minutes to pass and bond the parts together by pressing them firmly. Use clamps for 2-4 hours for better adhesion of all wood surfaces. Full bonding is achieved after 24 hours.

### ■ LIMITATION OF USE

It is not recommended to use the adhesive when the temperature is below +8°C. While the adhesive is still fresh, the temperature should not drop below +4°C.

### ■ CLEANING

Remove any excess glue immediately with a clean, wet cloth or a damp sponge. Clean all tools and hands with warm water.

### ■ CONSUMPTION

Depending on the absorbency and the nature of the surface.




---

## Crystal clear wood & paper glue

### ■ STORAGE

Store in the factory sealed packaging, in places protected from frost and heat, for 18 months from production date.

### ■ SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

### ■ PACKAGING

Carton box with 20 bottles of 110gr each one.

<b>TECHNICAL SPECIFICATIONS</b> (Measurement conditions 23°C and 50% R.H.)	
■ <b>Composition</b>	Viscous PVA
■ <b>Color</b>	White, becomes transparent when dry
■ <b>Density</b>	1.07±0.06kg/lt
■ <b>Solids by weight</b>	45% w/w
■ <b>Application temperature</b>	From +8°C to +35°C
■ <b>Adhesion strength</b>	3.5 N/mm <sup>2</sup> , after 48 hours (measurements on soft woods)

**DUROSTICK S.A.,**  
 MANUFACTURING OF ADHESIVES,  
 PAINTS & MORTARS  
**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,  
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,  
 +30 210 55 98 350, Fax: +30 210 55 99 612  
**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,  
 STREET, DA 10, GR: 570 22,  
 Tel: +30 2310 795 797, +30 2310 797 365,  
 Fax: +30 2310 797 367  
 Email: [info@durostick.com](mailto:info@durostick.com)