

**DECLARATION OF PERFORMANCE**

No. 168

1. Unique identification code of the product-type: **D-1 AQUA**
2. Intended use/es: **Surface protection product - Coating, Principle 2 (Moisture control) - Method 2.3/ Principle 5 (Physical resistance) - Method 8.3 according to EN 1504-9:2008**
3. Manufacturer: **DUROSTICK S.A., Paint, mortar & adhesive industry.**  
Production factory: **Patima Kororemi Aspropyrgos, Attica, PC.: 19300 Greece, www.durostick.gr**
4. Authorised Representative:
5. System/s of AVCP: **System 4**
6. Harmonised standard: **EN 1504-2:2004**
7. Declared performance/s:

Essential Characteristics	Performance
Reaction to fire	Class A1
Permeability to water vapour	Class I, $S_D < 5 \text{ m}$
Capillary absorption and permeability to water	$w \leq 0.1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$
Adhesion strength by pull off test	$\geq 1.0 \text{ N/mm}^2$
Dangerous substances	Comply with 5.3


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
**Zoi Athanasiou - Head of Mortar Lab**



Aspropyrgos **19.01.2024**

CE MARKING



**DUROSTICK S.A.**  
ASPROPYRGOS-ATHENS PC: 19300  
GREECE

24

DoP No. : 168

EN 1504-2:2004

**D-1 AQUA**

Surface protection product  
Coating

Permeability to water vapour	Class I, $S_b < 5$ m
Capillary absorption and permeability to water	$w \leq 0.1 \text{ kg} / \text{m}^2 \cdot \text{h}^{0,5}$
Adhesion strength by pull off test	$\geq 1.0 \text{ N/mm}^2$
Reaction to fire	Class A1
Dangerous substances	Comply with 5.3