ALUMINIUM CLEANER



Cleaning agent for aluminum surfaces



■ PROPERTIES

Powerful active cleaner. With just one spray, it easily removes pollutants from exhaust gases, salts, dirt, mud rain, and fresh emulsion paint splashes (2-3 days old at the most).

APPLICATIONS

DUROSTICK Aluminum CLEANER is ideal for use on unpainted, anodized or powder coated aluminum frames, without altering or affecting their original color.

■ USE

Preventive spot application is recommended, ideally in a hidden part of the surface to be cleaned, to verify the stability of the color of the aluminum surface to be cleaned.

Subsequently, spray the aluminum parts that require cleaning and scrub lightly with a soft, cotton cloth or sponge.

Allow the product to act for 1-2 minutes and rinse with clean water and a sponge. Dry the clean surfaces with a cotton cloth.

■ STORAGE

Store in shaded places, protected from sunlight and frost, for 36 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation.

However, it is recommended to keep away from the reach of children. If swallowed seek immediate medical advice and show the container or label.

PACKAGING

Paper box with 12 pcs of 500ml each one.

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

ALUMINIUM CLEANER



Cleaning agent for aluminum surfaces

| TECHNICAL SPECIFICATIONS | |
|--------------------------|---|
| Form - Color | Liquid - Transparent |
| ■ Density | 1.00±0.05kg/lt |
| ■ pH | 9±1 |
| ■ Contains | Phosphates less than 5%, anionic surfactants less than 5% |

Permit No. by General Chemical State Laboratory

ELEFSIS: 3093/2008

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,

PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 10, GR: 570 22,

Tel: +30 2310 795 797, +30 2310 797 365,

Fax: +30 2310 797 367 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.