D-19 GRAFFITI REMOVER



Powerful graffiti remover



■ PROPERTIES

Extra powerful graffiti remover.

It cleans surfaces made of metal and glass, concrete as well as plaster, marble, tiles and stone. It removes graffiti quickly and easily without leaving

It removes graffiti quickly and easily without leaving any stains and without damaging the painted surface. It cleans walls soiled with spray paint, permanent markers or ball-point pens in areas such as children's rooms.

APPLICATIONS

D-19 GRAFFITI REMOVER of DUROSTICK is suitable for almost any surface. Cleaning graffiti from school surfaces and university facilities or public and private buildings with D-19 GRAFFITI REMOVER is particularly cost effective compared to repainting.

It is also suitable for cleaning archaeological sites and monuments.

■ USE

DUROSTICK D-19 GRAFFITI REMOVER is an extra powerful graffiti remover.

During application and even rinsing, the use of protective gloves is recommended.

Spray from a distance of 20-25cm and clean with a soft cloth or sponge, depending on the surface. After removing the graffiti, rinse the surfaces with clean water. If necessary, repeat the process on porous surfaces with bold and persistent stains.

■ CONSUMPTION

Approximately 500ml/3m² of surface.

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

D-19 GRAFFITI REMOVER



Powerful graffiti remover

■ STORAGE

Store in places with low humidity, away from any heat source, for 36 months from production date.

■ SAFETY DIRECTIONS

The product is classified as harmful. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 15 pcs of 500ml each one 5lt container.

| TECHNICAL SPECIFICATIONS | |
|---------------------------|----------------------|
| Form - Color | Liquid - Transparent |
| ■ Density | 1.03±0.08kg/lt |
| ■ Application temperature | From +5°C to +35°C |

Permit No. by General Chemical State Laboratory ELEFSIS 3093/2008

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,

PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 10, GR: 570 22,

Tel: +30 2310 795 797, +30 2310 797 365,

Fax: +30 2310 797 367 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.