D-301 MULTI CLEANER



General purpose cleaner



■ PROPERTIES

Multipurpose cleaner, suitable for commercial and residential use. It evaporates quickly, without leaving any residue on surfaces. It instantly removes most pollutants with a simple swipe, compared to water-soluble cleaners.

APPLICATIONS

DUROSTICK D-301 helps remove dirt and oils from sensitive objects and difficult places on electronic boards, magnetic heads, optical media, computer components, keyboards, and all electronic devices. It deeply cleans smudges, grease, and oils, and degreases metal surfaces to be painted. For very soiled surfaces, soaking a cloth helps. Residues from

paints, markers, or silicones, as long as they have not solidified, are easily cleaned from surfaces or hands. Stainless steel, galvanized surfaces sparkle without rinsing or washing with water. It can be used to degrease car engines (after they have cooled down), chains, gears before they are lubricated, and all kinds of agricultural machinery.

■ USE

Apply it easily by spraying a sufficient amount and if necessary, remove any residue with a cloth.

■ CONSUMPTION

Depending on the application.

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

D-301 MULTI CLEANER



General purpose cleaner

■ STORAGE

Store in places protected from high temperatures and UV radiation, away from any heat source, for 18 months from production date.

■ SAFETY DIRECTIONS

The product is classified as flammable and an irritant. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 12 pcs of 1lt each one.

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
■ Density	0.79±0.05 kg/l
■ pH	7.0±0.5
Application temperature	From +5°C to +35°C

Permit No. by General Chemical State Laboratory

ELEFSIS: 3093/2008

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,

PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 10, GR: 570 22,

Tel: +30 2310 795 797, +30 2310 797 365,

Fax: +30 2310 797 367 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.