SPRAY TAR & TREE RESIN REMOVING SPRAY





■ PROPERTIES

Cleaning product that removes tar and stuck insect stains quickly and easily with a single spray. Ideal for dissolving and removing pine tree resin without discoloring or dulling the surfaces it is applied on.

APPLICATIONS

The TAR & TREE RESIN REMOVING SPRAY of DUROSTICK is suitable for any part of the automobile, even for wheels and rims, plastic and glass.

Removes tar from boat fender from luxury boats, as well as from the waterline of boats, when the boat remains stationary for a long time.

■ USE

Press the valve lightly and spray the area/spot to be cleaned.

Wipe clean using a damp sponge within a few seconds and thoroughly rinse the cleaned surface with plenty of water.

■ STORAGE

Store in shaded places away from any heat source, for 60 months from production date.

■ SAFETY DIRECTIONS

The product is classified as an irritant. It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 24 pcs of 180ml each one.

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

SPRAY TAR & TREE RESIN REMOVING SPRAY



TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
■ Density	0.97±0.03kg/lt
■ Contains	Anionic surfactants less than 5% Non-ionic surfactants less than 5%

Permit No. by General Chemical State Laboratory

ELEFSIS: 3093/2008

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,

PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 10, GR: 570 22,

Tel: +30 2310 795 797, +30 2310 797 365,

Fax: +30 2310 797 367 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.