

20' EPOXY ADHESIVE



In stick form



■ PROPERTIES

Two-component epoxy adhesive and putty, in stick form. It welds, repairs and seals similar and dissimilar materials. Materials such as metal, wood, marble and concrete, fiberglass, as well as ceramic, porcelain, etc. It does not adhere to polyethylene and teflon. Its convenient packaging, its bonding power and ability to be sanded and painted, make it essential for hundreds of applications. Classified R1T per EN 12004.

■ ADVANTAGES

- Easy and quick application.
- Powerful bonding, sealing, repairing ability.
- Exceptional temperature resistance (up to +115°C).
- Exceptional resistance to most chemicals.

■ APPLICATIONS

Countless applications for professionals such as plumbers, machinists and fitters, as well as refrigeration and auto body technicians. Also has

limitless applications for the DIY crowd. It is ideal for any kind of bonding, sealing and waterproofing in the house, car or boat. It is suitable for sealing holes and cracks, for sealing radiator leaks, as well as water and fuel tanks. It permanently repairs oil pans, and car radiators. Necessary in boating and yachting projects and repairs, it also seals washing machine drums etc.

■ USE

Remove any dust, oils, rust or loose materials from the surfaces. Cut as much material as needed and mix it with your fingers until fully homogenized. Apply to the surface immediately and smooth with a wet finger or sponge, if desired.

Clean any residue with alcohol or water, immediately after use. Paintable after 30 minutes.

Store the remaining product in its packaging.

■ CONSUMPTION

Depending on the application.

20' EPOXY ADHESIVE



In stick form

■ STORAGE

Store in shaded places of low humidity, for 18 months from production date.

■ SAFETY DIRECTIONS

The product is classified as an irritant and a corrosive. It is recommended to keep it locked away from the reach of children. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ NOTES

- Epoxy systems are susceptible to temperature and humidity until fully hardened. Increased temperatures will reduce the pot life of the mixture, while high humidity levels can cause matte or discolored spots on the surface and increase curing time.
- During and after mixing the two components together, the temperature of the mixture increases.
- Mix the two components thoroughly until homogeneous is achieved (one color), before applying.

■ PACKAGING

Carton box with 12 pcs of 56gr each one.

TECHNICAL SPECIFICATIONS

■ Color	A=Green, B=White, Final: Light green
■ Workability	4-7 minutes
■ Setting time	20 minutes at 25°C
■ Moisture resistance	Excellent
■ Resistant to organic solvents, acids and alkalis	Excellent
■ Temperature resistance	From -30°C to +115°C
■ Resistance to ageing	Excellent
■ Shrinkage	Negligible
■ Tensile strength	45 N/mm ²
■ Compressive strength	130 N/mm ²
■ Can be painted with any coating	Yes

DUROSTICK S.A.,
 MANUFACTURING OF ADHESIVES,
 PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
 Tel: +30 211 60 03 500-599, +30 210 55 16 500,
 +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 10, GR: 570 22,
 Tel: +30 2310 795 797, +30 2310 797 365,
 Fax: +30 2310 797 367
 Email: info@durostick.com