ADHESIVE FOR FOAM INSULATION TUBES





PROPERTIES

Powerful neoprene and synthetic resin adhesive. It provides powerful adhesion and flexible bonding to foam insulation materials, so as to withstand temperature variations. The container cap has a builtin round brush for easy application.

APPLICATIONS

DUROSTICK ADHESIVE FOR FOAM INSULATION TUBES is suitable for post-installation protection of foam insulation tubes on unprotected existing piping systems exposed to frost, such as piping for solar water heaters and metal or PVC garden pipes and pipes for transferring hot water.

USE

1. Surface preparation

Using a razor blade, slice one side of the foam insulation. Split open with your fingers and wrap it around the pipes for protection.

2. Application

Before use, shake the container well and apply a thin layer of adhesive on both sides of the foam insulation. Allow for the adhesive to set for 10 minutes and then press the two sides together. Close the container tightly after use.

CONSUMPTION

Depending on the application.

STORAGE

Store in tightly closed containers, in shaded places, away from any heat source, for 18 months from production date.

SAFETY DIRECTIONS

The product is classified as highly flammable and harmful.

It is recommended to keep away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product's packaging or the Safety Data Sheet.

PACKAGING

Carton box with 12pcs of 200ml each one.

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.

ADHESIVE FOR FOAM INSULATION TUBES



TECHNICAL SPECIFICATIONS	
Form - Color	Thixotropic liquid - Honey
Density	0.80±0.04kg/lt
Application temperature	From +5°C to +35°C
Temperature resistance	From -20°C to +70°C

DUROSTICK S.A., MANUFACTURING OF ADHESIVES, PAINTS & MORTARS ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612 THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367 Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.