



DECLARATION OF PERFORMANCE

No. 076 : HYDROSTOP SILICONE PLASTER FINE

1. Unique identification code of the product:

076

2. Intended uses:

Silicone based waterproof top coat plaster/render in paste form, fine

3. Manufacturer:

DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA

KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE, www.durostick.gr

4. Authorized representative:-

5. System of AVCP (assessment and verification of constancy of performance):

System 4

6a. Harmonized standard:

EN 15824 : 2017

6b. European Assessment Document: - European Technical Assessment: -
Technical Assessment Body: - Notified Body: -

7. Declared performance:

Essential characteristics	Declared performance	TEST METHOD
Water vapour permeability	V1	EN ISO 7783
Water absorption	W3	EN 1062-3
Adhesion	0,4 MPa	EN 1542
Durability	NPD	
Thermal conductivity	$\lambda = 0,7 \text{ W/(m} \cdot \text{K)}$	EN 1745
Reaction to fire	Euroclass C	EN 13501-1
Dangerous substances	According to paragraph 4.8	

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

KOUTSIBELIS ARISTIDES

Aspropyrgos, 10/11/2022

Manager Research & Quality Assurance

CE MARKING ACCORDING TO CPR 305/2011 AND EN 15824 : 2017



**DUROSTICK S.A
ASPROPYRGOS ATHENS PC: 19300, GREECE**

13

HYDROSTOP SILICONE PLASTER FINE

DoP No. : 076

EN 15824

External render based on organic binder

Water vapour permeability: V1

Water absorption: W3

Adhesion: 0,4 MPa

Durability: NPD

Thermal conductivity: $\lambda = 0,7 \text{ W/(m} \cdot \text{K)}$

Reaction to fire: Euroclass C

Dangerous substances: According to paragraph 4.8