



DECLARATION OF PERFORMANCE

No. 112 : DUROSTICK NEUTRAL SILICONE

1. Unique identification code of the product:
112
2. Intended uses:
Silicone for permanent water immersion
3. Manufacturer:
**DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA
KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE, www.durostick.gr**
4. Authorized representative:-
5. System of AVCP (assessment and verification of constancy of performance):
System 3
- 6a. Harmonized standard:
EN 15651-1, EN 15651-3, EN 13501-1:2007+A1:2010 Notified Body: The notified control laboratory Tecnalía Research & Innovation with number (1292) has carried out initial tests to determine the product type under system 3 and issued a test report with number No 14_05998-1-a, No 14_05998-2-a, 14_08336-10-a.
- 6b. European Assessment Document: - European Technical Assessment: -
Technical Assessment Body: - Notified Body: -
7. Declared performance:

PROCEDURE A (ACCORDING TO ISO 8339)

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	Class E	
Release of Chemicals	None	See product safety data sheet
Resistance to flow	≤3mm	EN 15651-1,3:2012
Loss of volume	≤20%	EN 15651-1,3:2012
Tensile properties at maintained extension T=23°C	No Failure	EN 15651-1,3
Tensile properties at maintained extension T=-20°C	No Failure	EN 15651-1
Tensile properties after immersion in water	No Failure	EN 15651-1,3
Adhesion/cohesion properties at variable temperatures	No Failure	EN 15651-1,3
Durability	Pass	EN 15651-1,3

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

KOUTSIBELIS ARISTIDES

Aspropyrgos, 13/12/2022

Manager Research & Quality Assurance



DUROSTICK S.A

ASPROPYRGOS ATHENS PC: 19300

GREECE

14

DoP No. : 112

EN 15651-1,3

DUROSTICK NEUTRAL SILICONE

Reaction to fire : Class E

Release of Chemicals : None

Resistance to flow: $\leq 3\text{mm}$

Loss of volume: $\leq 20\%$

Tensile properties at maintained extension T=23°C : No Failure

Tensile properties at maintained extension T=-20°C: No Failure

Tensile properties after immersion in water: No Failure

Adhesion/cohesion properties at variable temperatures: No Failure

Durability: Pass