



## DECLARATION OF PERFORMANCE

DoP [EN] No. 005 DURO-CPR-7-2013

1. Unique identification code of product-type:  
**DUROSTICK ACRYLIC tile adhesive.**
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):  
**The coding shown on the packaging is the production date of the product.**
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:  
**Enhanced tile adhesive with reduced slip and extended open time C2TE.**
4. Name, registered name or registered trade mark and contact address for the manufacturer as required to Article 11(5):  
**DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE**
5. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:  
**Not applicable.**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
**System 3.**
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:  
**EN 12004: 2007+ A1: 2012**  
The notified control laboratory MIRTEC with number NB 0437 has carried out initial tests to determine the product type under system 3 and issued a test report with number 3353.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
**Not applicable.**
9. Declared performance:

Essential characteristics	Declared performance	Harmonised standard Appropriate /Technical Documentation	
Reaction to fire:	<b>Euroclass (A1/A1<sub>fl</sub>)</b>		
Bond Strength as:	<b>&gt; 1N/mm<sup>2</sup></b>	<b>EN 1348 8.2</b>	<b>EN 12004:2007+A1:2012</b>
• Tensile adhesion strength			
Durability as:			
Tensile adhesion strength after:			
• heat ageing	<b>&gt; 1N/mm<sup>2</sup></b>	<b>EN 1348 8.4</b>	
• water immersion:	<b>&gt; 1N/mm<sup>2</sup></b>	<b>EN 1348 8.3</b>	
• freeze-thaw cycles:	<b>&gt; 1N/mm<sup>2</sup></b>	<b>EN 1348 8.5</b>	
Dangerous substances	<b>See MSDS</b>		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
**Signed for and on behalf of the manufacturer:**

Evdoxia Kafritsa

Aspropyrgos 12/12/2016

R&D Manager, QC mortars lab



**DUROSTICK S.A**

**ASPROPYRGOS ATHENS PC: 19300**

**GREECE**

**07**

**EN 12004:2007+ A1:2012**

**DUROSTICK ACRYLIC**

**DoP No.: 005**

**C2TE**

**Enhanced adhesive with reduced slip**

**and extended open time**

**Interior –exterior use**

- Reaction to fire: Euroclass A<sub>1</sub>
- Release of dangerous substances: see MSDS

**Bond Strength as:**

- Tensile adhesion strength :  $\geq 1.00 \text{ N/mm}^2$

**Durability for:**

- Tensile adhesion strength

after heat ageing:  $\geq 1.00 \text{ N/mm}^2$

- Tensile adhesion strength

after water immersion:  $\geq 1.00 \text{ N/mm}^2$

- Tensile adhesion strength

after freeze-thaw cycles:  $\geq 1.00 \text{ N/mm}^2$