



DECLARATION OF PERFORMANCE

No. 064 DURO-CPR-7-2013 : HYDROSTOP PLASTER D74

1. Unique identification code of the product:
064
2. Intended uses: **EN 998-1: General purpose rendering/plastering mortar.**
3. Manufacturer:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE, www.durostick.gr
4. Authorized representative:-
5. System of AVCP (assessment and verification of constancy of performance):
System 4
- 6a. Harmonized standard:
EN 998-1:2016

Notified body: -

- | | | | |
|----------------------------------|-----------------------|-------------------------------|-----------------------|
| 6b. European Assessment Document | not applicable | European Technical Assessment | not applicable |
| Technical Assessment Body | not applicable | Notified Body | not applicable |

7. Declared performance


Essential characteristics	Performance	Test method/ Harmonised Standard	
Reaction to fire	Euroclass A1	EN 13501-1	
Compressive strength	CS III :3,5- 7.5N/mm ²	EN 1015-11	EN 998-1:2016
Capillary water absorption	W2: ≤ 0.20 kg/m ² . min ^{0.5}	EN 1015-18	
Adhesion	≥ 0.72 N/mm ²	EN 1015-12	
Water vapour permeability	μ 15/35	EN 1015-21	
Thermal conductivity λ _{10,dry} (P=50%)	0.75 W/K.m	EN 1745-TablA.12	
Durability	evaluation based on provisions valid in the intended place of use of the mortar	EN 998-1:§5.3.2.2	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not applicable**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Evdoxia Kafritsa
 Function: Head of R&D, QC Mortars Dept.
 Place/Date: Aspropyrgos/ 2nd of January 2019

	
DUROSTICK S.A ASPROPYRGOS ATHENS PC: 19300 GREECE 08	
DoP No: 064 EN 998-1:2016	
HYDROSTOP PLASTER DS-74 General purpose plastering/rendering mortar GP: CSIII/W2	
Reaction to fire :	Euroclass A1
Adhesive strength :	≥0.72 N/mm² FP: B
Water absorption:	W2
Water vapour diffusion coefficient:	μ 15/35
Dry Bulk Density:	1710 kg/m³
Thermal conductivity (λ_{10, dry}):	0.75 W/m·K (Table value P=50%)
Durability (against freeze/thaw): evaluation based on provisions valid in the intended place of use of the mortar	
Release of dangerous substances: see MSDS	

The CE marking shown in this Declaration of Performance is the most recent, in accordance with the current regulation. Possible variations of the present marking with the corresponding one appearing on the packaging or the Technical Data Sheet may be due to the following reasons:

- *The packaging was already printed before the latest CE revision.*
- *Printing error*
- *Differences due to packaging sizes and printing method.*