



DECLARATION OF PERFORMANCE

No. 066 DURO-CPR-7-2013 : HYDROSTOP PLASTER ELASTIC fine

1. Unique identification code of the product:
066
2. Intended uses: **EN 998-1: General purpose rendering/plastering mortar.**
3. Manufacturer:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE, www.durostick.gr
4. Authorized representative:-
5. System of AVCP (assessment and verification of constancy of performance):
System 4
- 6a. Harmonized standard:
EN 998-1:2016

Notified body: -

- 6b. European Assessment Document **not applicable** European Technical Assessment **not applicable**
 Technical Assessment Body **not applicable** Notified Body **not applicable**

7. Declared performance


Essential characteristics	Performance	Test method/ Harmonised Standard	
Reaction to fire	Euroclass F	EN 13501-1	
Compressive strength	CS III :3,5- 7.5N/mm ²	EN 1015-11	EN 998-1:2016
Capillary water absorption	W2: ≤ 0.20 kg/m ² . min ^{0.5}	EN 1015-18	
Adhesion	≥ 0.80 N/mm ²	EN 1015-12	
Water vapour permeability	μ 15/35	EN 1015-21	
Thermal conductivity λ _{10,dry} (P=50%)	0.58 W/K.m	EN 1745-TablA.12	
Durability	evaluation based on provisions valid in the intended place of use of the mortar	EN 998-1:§5.3.2.2	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not applicable**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Evdoxia Kafritsa
 Function: Head of R&D, QC Mortars Dept.
 Place/Date: Aspropyrgos/ 15th of January 2019

	
DUROSTICK S.A ASPROPYRGOS ATHENS PC: 19300 GREECE 10	
DoP No: 066 EN 998-1:2016	
HYDROSTOP PLASTER ELASTIC fine General purpose plastering/rendering mortar GP: CSIII/W2	
Reaction to fire :	Euroclass F
Adhesive strength :	≥0.80 N/mm² FP: B
Water absorption:	W2
Water vapour diffusion coefficient:	μ 15/35
Dry Bulk Density:	1560 kg/m³
Thermal conductivity (λ_{10, dry}):	0.58 W/m·K (Table value P=50%)
Durability (against freeze/thaw):	evaluation based on provisions valid in the intended place of use of the mortar
Release of dangerous substances:	see MSDS

The CE marking shown in this Declaration of Performance is the most recent, in accordance with the current regulation. Possible variations of the present marking with the corresponding one appearing on the packaging or the Technical Data Sheet may be due to the following reasons:

- The packaging was already printed before the latest CE revision.
- Printing error
- Differences due to packaging sizes and printing method.

