



## DECLARATION OF PERFORMANCE

No. 006 DURO-CPR-7-2013 : **SUPER ACRYLIC**

1. Unique identification code of the product:  
**006**
2. Intended uses: **EN 12004-1:2017 : Improved cementitious adhesive with reduced slip and extended open time, C2TE. All internal and external wall and floor tiling.**
3. Manufacturer:  
**DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE, [www.durostick.gr](http://www.durostick.gr)**
4. Authorized representative:-
5. System of AVCP (assessment and verification of constancy of performance):  
**System 3**
- 6a. Harmonized standard:  
**EN 12004-1:2017**  
Notified body:  
**The laboratory MITREC , notified body NB 0437, performed Initial testing under system 3 and issued test report No. 3354**
- 6b. European Assessment Document **not applicable** European Technical Assessment **not applicable**  
Technical Assessment Body **not applicable** Notified Body **not applicable**

### 7. Declared performance

Essential Characteristics	Classes and/or threshold levels	Harmonized Standard /test method
Reaction to fire	Class E(CWFT*)	EN 12004-1:2017
Bond strength expressed as:		
• Initial tensile adhesion strength:	≥1.00N/mm <sup>2</sup>	
Durability of bond expressed as tensile adhesion after:		
• heat ageing	≥1.00N/mm <sup>2</sup>	
• water immersion	≥1.00N/mm <sup>2</sup>	EN 12004-2:2017
• freeze-thaw cycles	≥1.00N/mm <sup>2</sup>	
Release of dangerous substances	see MSDS	


\* CWFT: Classified without further testing

### 7. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not applicable**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Evdoxia Kafritsa  
Function: Head of R&D, QC Mortars Dept.  
Place/Date: Aspropyrgos/ 2<sup>nd</sup> of January 2019

	
<b>DUROSTICK S.A</b> <b>ASPROPYRGOS ATHENS PC: 19300</b> <b>GREECE</b> <b>07</b>	
<b>EN 12004-1:2017</b> <b>SUPER AKPYAIKH</b> <b>DoP No.: 006</b> <b>C2TE</b>  Improved cementitious adhesive  with reduced slip and extended open time  All internal and external wall and floor tiling	
<b>- Reaction to fire:</b>	<b>Class E(CWFT)</b>
<b>- Release of dangerous substances:</b>	<b>see MSDS</b>
<b>Bond Strength as:</b>	
<b>- Initial tensile adhesion strength :</b>	<b>≥1.00 N/mm<sup>2</sup></b>
<b>Durability of bond expressed as :</b>	
<b>- Tensile adhesion strength after heat ageing:</b>	<b>≥1.00 N/mm<sup>2</sup></b>
<b>- Tensile adhesion strength after water immersion:</b>	<b>≥1.00 N/mm<sup>2</sup></b>
<b>- Tensile adhesion strength after freeze-thaw cycles:</b>	<b>≥1.00 N/mm<sup>2</sup></b>