



DECLARATION OF PERFORMANCE

DoP [EN] No. 012 DURO-CPR-7-2013

1. Unique identification code of product-type:
D U R O S T I C K D - 6
2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):
The coding shown on the packaging is the production date of the product.
3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:
Fiber reinforced floor screed for application thicknesses from 2-5cm per coat.
4. Name, register name or register trade mark and contact address for the manufacturer as required to Article 11:
DUROSTICK S.A., PAINT, MORTAR & ADHESIVE INDUSTRY, PATIMA KOROREMI ASPROPYRGOS, ATTICA, PC.: 19300 GREECE
5. Where applicable, name and contact address of the authorized representative whose mandate covers the task specified in Article 12:
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4.
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
EN 13813: 2002
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable.
9. Declared performance:

Essential characteristics	Declared performance	Harmonized Technical specification
Reaction to fire	Euroclass 1	
Release of corrosive substances	CT	
Water permeability	NPD	EN 1062-3
Water vapour permeability	NPD	EN 12086
Compressive strength	C20	EN 13892-2
Flexural strength	F4	EN 13892-2
Wear resistance	BCA: AR4	EN 13892-4
Sound insulation/ Sound absorption	NPD	EN ISO 140-6/ N ISO 354
Thermal resistance/ chemical resistance	NPD	EN 12664/ EN 13529

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Evdoxia Kafritsa



Aspropyrgos 11/07/2013

R&D Manager, QC mortars lab



**DUROSTICK S.A
ASPROPYRGOS ATHENS PC: 19300
GREECE
09**

EN 13813 CT20-F4-AR4-A_{1fl}

**DUROSTICK D-6
DoP No. : 012**

**Cementitious screed material for use
Internally/externally in buildings**

Reaction to fire:	Euroclass A1
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C20
Flexural strength:	F4
Wear resistance, BCA:	AR4
Sound insulation/ Sound absorption:	NPD
Thermal resistance/ Chemical resistance:	NPD