

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

20 MINUTE EPOXY ADHESIVE



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 20 MINUTE EPOXY ADHESIVE

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: EPOXY ADHESIVE-PUTTY IN STICK FORM

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

DUROSTICK SA
PATIMA KOROREMI
193 00 ASPROPIRGOS, ATTICA - GREECE
Phone: 211 60 03 500-599 - Fax: 210 55 99 612
info@durostick.gr
www.durostick.gr

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Dam. 1: Serious eye damage, Category 1, H318

Resp. Sens. 1: Sensitisation, respiratory, Category 1, H334

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P285: In case of inadequate ventilation wear respiratory protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P363: Wash contaminated clothing before reuse.

P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

20 MINUTE EPOXY ADHESIVE



SECTION 2: HAZARDS IDENTIFICATION ** (continued)

Supplementary information:

Contains 2,2'-iminodiethylamine, reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100).

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives and epoxy polymers

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 25068-38-6 EC: 500-033-5 Index: 603-074-00-8 REACH: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100)⁽¹⁾ Self-classified	10 - <25 %
	Regulation 1272/2008 Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	
CAS: 111-40-0 EC: 203-865-4 Index: 612-058-00-X REACH: 01-2119473793-27-XXXX	2,2'-iminodiethylamine⁽¹⁾ ATP CLP00	2,5 - <10 %
	Regulation 1272/2008 Acute Tox. 4: H302+H312; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	
CAS: 96-27-5 EC: 202-495-0 Index: Non-applicable REACH: 01-2120768144-53-XXXX	3-mercaptopropane-1,2-diol⁽¹⁾ Self-classified	1 - <2,5 %
	Regulation 1272/2008 Acute Tox. 3: H311; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

20 MINUTE EPOXY ADHESIVE



SECTION 4: FIRST AID MEASURES (continued)

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

20 MINUTE EPOXY ADHESIVE



SECTION 7: HANDLING AND STORAGE (continued)

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
 Maximum Temp.: 30 °C
 Maximum time: 18 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100) CAS: 25068-38-6 EC: 500-033-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,75 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4,93 mg/m ³	Non-applicable
2,2'-iminodiethylamine CAS: 111-40-0 EC: 203-865-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	11,4 mg/kg	Non-applicable
	Inhalation	92,1 mg/m ³	2,6 mg/m ³	15,4 mg/m ³	0,87 mg/m ³
3-mercaptopropane-1,2-diol CAS: 96-27-5 EC: 202-495-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,14 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,49 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100) CAS: 25068-38-6 EC: 500-033-5	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,0893 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,87 mg/m ³	Non-applicable
2,2'-iminodiethylamine CAS: 111-40-0 EC: 203-865-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	4,88 mg/kg	Non-applicable	4,88 mg/kg	Non-applicable
	Inhalation	27,5 mg/m ³	Non-applicable	4,6 mg/m ³	Non-applicable
3-mercaptopropane-1,2-diol CAS: 96-27-5 EC: 202-495-0	Oral	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,074 mg/m ³	Non-applicable

PNEC:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

20 MINUTE EPOXY ADHESIVE



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Identification				
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100) CAS: 25068-38-6 EC: 500-033-5	STP	10 mg/L	Fresh water	0,006 mg/L
	Soil	0,065 mg/kg	Marine water	0,001 mg/L
	Intermittent	0,018 mg/L	Sediment (Fresh water)	0,341 mg/kg
	Oral	0,011 g/kg	Sediment (Marine water)	0,034 mg/kg
2,2'-iminodiethylamine CAS: 111-40-0 EC: 203-865-4	STP	6 mg/L	Fresh water	0,56 mg/L
	Soil	7,97 mg/kg	Marine water	0,056 mg/L
	Intermittent	0,32 mg/L	Sediment (Fresh water)	1072 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	107,2 mg/kg
3-mercaptopropane-1,2-diol CAS: 96-27-5 EC: 202-495-0	STP	Non-applicable	Fresh water	0,006 mg/L
	Soil	Non-applicable	Marine water	0,001 mg/L
	Intermittent	0,057 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:



A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

- CONTINUED ON NEXT PAGE -

Safety data sheet



This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



20 MINUTE EPOXY ADHESIVE

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Amorphous
Colour:	<input type="checkbox"/> White (B) / Green (A)
Odour:	Odourless
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	218 °C
Vapour pressure at 20 °C:	16 Pa
Vapour pressure at 50 °C:	127,86 Pa (0,13 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	1935,4 kg/m ³
Relative density at 20 °C:	1,935
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



20 MINUTE EPOXY ADHESIVE

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Oxidising properties:	Non-applicable *
Flammability:	
Flash Point:	Non Flammable (>60 °C)
Heat of combustion:	Non-applicable *
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	358 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Explosive:	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
9.2 Other information:	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

20 MINUTE EPOXY ADHESIVE



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Prolonged exposure can result in specific respiratory hypersensitivity.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
2,2'-iminodiethylamine CAS: 111-40-0 EC: 203-865-4	LD50 oral	500 mg/kg (ATEi)	
	LD50 dermal	1100 mg/kg (ATEi)	
	LC50 inhalation	Non-applicable	
3-mercaptopropane-1,2-diol CAS: 96-27-5 EC: 202-495-0	LD50 oral	645 mg/kg	Rat
	LD50 dermal	670 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Not available

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100) CAS: 25068-38-6 EC: 500-033-5	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



20 MINUTE EPOXY ADHESIVE

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100)	BCF	4
CAS: 25068-38-6	Pow Log	2.8
EC: 500-033-5	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2,2'-iminodiethylamine	Koc	Non-applicable	Henry	Non-applicable
CAS: 111-40-0	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-865-4	Surface tension	4,164E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP13 Sensitising, HP8 Corrosive

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

- 14.1 UN number:** Non-applicable
- 14.2 UN proper shipping name:** Non-applicable
- 14.3 Transport hazard class(es):** Non-applicable
- Labels: Non-applicable
- 14.4 Packing group:** Non-applicable
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: Non-applicable
- Tunnel restriction code: Non-applicable
- Physico-Chemical properties: see section 9
- Limited quantities: Non-applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation



20 MINUTE EPOXY ADHESIVE

SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IMDG 39-18:



14.1 UN number:	UN1760
14.2 UN proper shipping name:	CORROSIVE LIQUID, N.O.S. (2,2'-iminodiethylamine)
14.3 Transport hazard class(es):	8
Labels:	8
14.4 Packing group:	II
14.5 Marine pollutant:	No
14.6 Special precautions for user	
Special regulations:	274
EmS Codes:	F-A, S-B
Physico-Chemical properties:	see section 9
Limited quantities:	1 L
Segregation group:	Non-applicable
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:



14.1 UN number:	UN1760
14.2 UN proper shipping name:	CORROSIVE LIQUID, N.O.S. (2,2'-iminodiethylamine)
14.3 Transport hazard class(es):	8
Labels:	8
14.4 Packing group:	II
14.5 Environmental hazards:	No
14.6 Special precautions for user	
Physico-Chemical properties:	see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

—tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of Regulation (EU) n° 2015/830, without any country-specific legislation

20 MINUTE EPOXY ADHESIVE



SECTION 15: REGULATORY INFORMATION (continued)

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H318: Causes serious eye damage.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H311 - Toxic in contact with skin.

Acute Tox. 4: H302 - Harmful if swallowed.

Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -