

DUROSTICK D-7



Natural stone cleaner



PROPERTIES

A powerful cleaner that removes construction residues from natural stones, restoring their natural look. It cleans in depth accumulated dirt, salts, mud rain, black spots, mold, as well as oil, coffee, rust and uncured paint stains. It does not affect the natural look of stones and/or grouts. Its use is necessary prior to waterproofing and/or decorating a surface with varnish.

APPLICATIONS

D-7 is used on walls and floors lined with natural stones. Before use, it is recommended to test the cleaner on a small, unseen area, particularly for stones sensitive to powerful cleaners (e.g. limestone). It is recommended to use the product 28 days after grouting. Its use is necessary for removing construction residues, prior to the application of the waterproofing agents RENOLIT or DUROSTICK NANO PROOF CERAMIC DS-270. It is also necessary before applying any DUROSTICK stone varnishes, such as D-72, D-12, VISTA, DECOFIN EPOXY SF or DECOFIN POLYURETHANE.

LIMITATION OF USE

Application of D-7 is not recommended for marble or artificial stones, and decorative bricks.

USE

1. Surface preparation

During application it is strongly recommended to use goggles and plastic gloves. In interior applications, open doors and windows to prevent vapour accumulation. Remove stainless steel utensils and protect stainless sinks, faucets, etc., with plastic sheeting. On exterior applications, make sure that residue accumulations near planted areas are avoided, since there is risk of harming them.

2. Application Apply D-7 on the surface as is, undiluted and scrub using a stiff broom. Let the product act for 3-5 minutes. Finish the process by rinsing thoroughly with plenty of water.

CONSUMPTION

1lt/4-5m² of surface.

DUROSTICK D-7



Natural stone cleaner

STORAGE

Store in shaded places, protected from frost for at least 36 months from production date.

SAFETY DIRECTIONS

The product is corrosive and irritant to the respiratory system. It is recommended to keep locked away from the reach of children and apply it in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

PACKAGING

Carton box with 15 pcs of 1lt each one
5 lt, 20lt containers

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Density	1.05±0.05kg/lt
pH	0-1
Application temperature	From +5°C to +35°C
Scent	Lemon
Flammable	No
Contains hydrochloric acid	
<i>General Chemical State Laboratory Reg. No. 5311/0/99</i>	
<i>Permit No. by General Chemical State Laboratory ELEFSIS 3093/2008</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:

+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55

98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.