

HYDROSTOP SILICONE PRIMER



Adhesion primer for plasters in paste form



PROPERTIES

Water soluble, silicone based, acrylic primer, suitable for silicone and acrylic plasters in paste form. It stabilizes and reduces the absorbency of surfaces resulting in the unbreakable adherence of all plasters in paste form.

APPLICATIONS

HYDROSTOP SILICONE PRIMER is ready to use on any porous surface, such as concrete and top coat plaster, gypsum board and cement board. Designed to work with silicone and acrylic plasters, such as HYDROSTOP SILICONE PLASTER and HYDROSTOP ACRYLIC PLASTER of DUROSTICK.

USE

1. Surface preparation

The surface to be primed must be dry and free of dust, grease, pollutants etc.

2. Application

Stir well HYDROSTOP SILICONE PRIMER and apply it undiluted. Coat the substrate evenly using a roller or a brush. Allow for the primer to dry

for at least three hours and continue with the plaster application.

CONSUMPTION

Approximately 8-10m²/lt per coat, depending on the absorbency of the substrate.

STORAGE

Store in closed containers, in places protected from frost and strong sunlight, for at least 12 months from production date.

SAFETY DIRECTIONS

The product needs no hazard labeling based on current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

5lt, 20lt containers

HYDROSTOP SILICONE PRIMER



Adhesion primer for plasters in paste form

TECHNICAL SPECIFICATIONS	
Form - Color	Emulsion - White, becomes transparent when dry
Density	1.00±0.05kg/lit
Drying time	3 hours at 20°C
Resistance	Resistance to concrete carbonation and alkaline environment
Odorless, friendly to human and the environment	
<i>V.O.C. (Volatile Organic Compounds): V.O.C. Limit of maximum V.O.C. content EC (Directive 2004/42/EC) for this product (category A/h: 'Binding primers' Type WB): 30gr/lit (2010). The ready to use product contains max 29gr/lit V.O.C.</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:

+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55

98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.