

ROMIX PROFESSIONAL



Emulsion paint



PROPERTIES

Water dispersion, emulsion paint that is low odor. Economical, ideal for frequent paint maintenance, as it dries and repaints quickly, creating a uniform matte white surface. Distinguished for its remarkable adhesion and coverage. It allows the breathability of the substrate and it is easily applied. It offers a reliable and affordable solution for professionals and consumers alike. Ideal for spaces in need of frequent maintenance.

APPLICATIONS

ROMIX PROFESSIONAL is applied on new and existing interior spaces to be painted made of plaster, gypsum board, MDF, spackled surfaces etc. Interior surfaces that require frequent painting and freshening up, such as large public projects, hotels, hospitals, gyms, schools, warehouses, etc. Suitable for painting surfaces such as walls, ceilings, stairwells, warehouses, etc.

USE

1. Substrate preparation

Surfaces from concrete and marble based plaster have to be dry, at least 30 days from their construction, and free from loose materials.

Surfaces soiled with soot and air pollution, are cleaned with the biodegradable cleaner BIO-CLEAN (for nicotine and soot) or they are primed with METAL PRIMER of DUROSTICK.

Already painted, sound surfaces two coats of ROMIX PROFESSIONAL of DUROSTICK are enough

2. Application

Dilute ROMIX PROFESSIONAL with water at a ratio of up to 5%, depending on the substrate, and stir well.

Apply with brush, roller or airless spray gun in 2-3 coats. Apply each additional coat, after the previous one is completely dry.

CLEANING

Clean all tools with water and detergent solution, immediately after use.

ROMIX PROFESSIONAL



Emulsion paint

PERFORMANCE

Approximately 9-12m²/lt per coat, depending on the texture, the absorbency of the surface and the application method.

STORAGE

Store in places protected from sunlight and frost, for at least 18 months from production date.

NOTE

If needed, it is recommended to clean the freshly painted surface that ROMIX PROFESSIONAL was used, with a soft sponge and mild detergent, 20 days after its application.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep the product away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs of 750ml each one
3lt container (on a 120 pcs pallet)
9lt container (on a 48 pcs pallet)

TECHNICAL SPECIFICATIONS	
Color	White that does not yellow over time
Shades	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors. The PAL base is colored via the COLOR COLLECTION System in any desired color.
Washability	> 10,000 cycles (per DIN 53778)
Gloss	Matte
Drying time	1 hour (touch dry), depending on the ambient conditions
Recoating time	4-5 hours, depending on the ambient conditions
Application temperature	From +8°C to +35°C
Flammable	No
V.O.C. (Volatile Organic Compounds): <i>Limit value of maximum V.O.C. content per EC (Directive 2004/42/EC) for the particular product (Class A/a: 'Matte coatings for interior walls and ceilings' Type WB): 30gr/lt (2010). The ready to use product contains maximum 29gr/lt V.O.C.</i>	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44, STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30 2310 797 365, Fax: +30 2310 797 367
E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.