

STUCOFIX



Ready to use acrylic putty



PROPERTIES

Water soluble white putty, based on acrylic styrene resins. It applies easily and smoothly. Dries quickly and sands easily without bursting creating a smooth and durable surface without defects.

ADVANTAGES

- Ready for use.
- Exceptional adhesion to concrete, plaster and wood.
- Great filling ability.
- Resistant to moisture and frost.

APPLICATIONS

STUCOFIX smooths out all surfaces made of gypsum and marble based plaster. It is also suitable for wood surfaces like doors, windows and even wood boats. It perfectly seals all nail holes on various surfaces.

USE

1. Surface preparation

Surfaces must be clean, dry and free from loose materials and oils. They also have to be dry for at least 30 days from their construction (for marble based plaster or concrete surfaces).

2. Application

Apply the product as is, using a putty knife. Apply one to two coats, 0.5mm thick each one. Apply the second coat once the first one is dry. Allow for 2-3 hours to pass and sand the surface using the appropriate sandpaper. The surface can be repainted with emulsion, acrylic paints or ripolin.

CLEANING

Clean all tools with water, immediately after use.

CONSUMPTION

1kg/2-3m², depending on the surface.

STUCOFIX



Ready to use acrylic putty

STORAGE

Store in the factory sealed packaging, in places protected from frost, for at least 18 months from date of production.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and National legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 24 pcs of 200gr each one
 Carton box with 18 pcs of 400gr each one
 Carton box with 24 pcs of 800gr each one
 5kg, 20kg containers

TECHNICAL SPECIFICATIONS	
Form-Color	Putty - White
Density	1.70±0.08kg/lt
Application temperature	From +8°C to +35°C
Painting/Wallpaper installation	After 24 hours
Friendly to human and the environment	

DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:
 +30 211 60 03 500-599, +30 210 55 16 500, +30 210 55
 98 350, Fax: +30 210 55 99 612

THESSALONIK: INDUSTRIAL PARK-SINDOS, S.B. 44,
 STREET, DA 0, GR: 570 22, Tel: +30 2310 795 797, +30
 2310 797 365, Fax: +30 2310 797 367

E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.