

# DUROSTICK ACID TILE CLEANER



For construction residues



## PROPERTIES

Powerful acid cleaner for removing construction residues. Dissolves and removes residues from excess grouts, tile adhesives and cements that were created during the application stages. Thoroughly cleans and removes stains from oils, coffee, drinks, lime, emulsion paints, rust etc. With minimal scrubbing, it removes pollutants accumulated over time in the grout joints, making their colors more vibrant.

## APPLICATIONS

DUROSTICK ACID TILE CLEANER works within minutes on walls and floors lined with ceramic tiles or sealed granite. Use the cleaner only after allowing at least for 20 days to pass from the grouting completion. It easily removes construction residues from tools.

## USE

### Preparation

Open doors and windows to prevent vapour accumulation. Protect eyes and hands using goggles and rubber gloves, respectively. Remove all

stainless steel utensils from the application, and adjacent, areas. Protect all non removable items, such as bathroom faucets, stainless steel sinks and anything else of similar materials, using plastic sheathing to cover everything up. This precautionary action will prevent oxidation of the materials from the vapours. It is highly advisable to test the product on a tile, before applying it to the surface (preventively). This is to avoid any possible corrosion or discoloration that very rarely occurs in exceptionally limited types of tiles.

### Application

The tile cleaner is applied undiluted to the surface. Using a stiff broom or a scrubbing sponge, scrub for 2-3 minutes and rinse with water thoroughly. Follow the same procedure to revitalize the color of stable and sound grouts.

## LIMITATION OF USE

The product is not recommended for cleaning decorative tiles, marble, any limestone and sanitary fixtures.

# DUROSTICK ACID TILE CLEANER



For construction residues

## CONSUMPTION

1lt/5-7m<sup>2</sup> of surface.

## STORAGE

Store in shaded places protected from frost, for at least 36 months from production date.

## SAFETY DIRECTIONS

The product is corrosive and an irritant to the respiratory system. Recommended to keep locked, away from the reach of children and apply in well ventilated areas. Before use, refer to the cautions on the product packaging or the Material Safety Data Sheet.

## PACKAGING

Carton box with 15 pcs. of 1lt each one 5lt, 20lt containers

| TECHNICAL SPECIFICATIONS  |                      |
|---|----------------------|
| Form - Color  | Liquid - Transparent |
| Density   | 1.05±0.05 kg/lt      |
| pH  | 0-1                  |
| Application temperature   | From +5°C to +35°C   |
| Scent:  | Lemon                |
| Flammable   | No                   |
| General Chemical State Laboratory 5312/0/99 Permit No. by General Chemical State Laboratory ELEFSIS 3093/2008 |                      |

## DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00, Tel:

+30 211 60 03 500-599, +30 210 55 16 500, +30 210 55

98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,

STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30

2310 797 365, Fax: +30 2310 797 367

E-mail: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.