

# DUROSTICK D-22



Water and oil repelling agent for marble & granite



## PROPERTIES

Siloxane based, waterproofing and oil repelling liquid with exceptional penetrating ability (micro technology). Its application creates an invisible surface film that does not peel off nor yellow and does not slip. Its application 'prevents' staining from oil, wine and soft drinks, ink, rust, as well as pet stains, air pollutants, etc.

## APPLICATIONS

D-22 is applied on facades made from marble and granite. Its application prevents the absorption of atmospheric pollutants for at least 4 years and makes cleaning easier. It is necessary for kitchen countertops and bathroom sinks, steps, as well as pebbles of various sizes and colors. It protects, over time, the historic and aesthetic value of statues and monuments. On lined walls and floors, it prevents salts and alkalis to rise to the surface and stain them. D-22 protects the surfaces from the absorption of stains within polished or honed marble on balconies or interior surfaces, after the watering of plants in pots of any size.

## USE

### Surface preparation

#### • Polished surfaces

Prior to the waterproofing and to reach the best result possible, clean the application surfaces using DUROSTICK BIOCLEAR, the biodegradable cleaner for polished marble and granite. Before waterproofing the surface(s), it is recommended to test it, so as to verify that the surface can absorb the material.

#### • Honed & unpolished surfaces

When working with unpolished or heavily stained marble, the use of DUROSTICK D-21 marble cleaner, is highly recommended.

### Application

Apply D-22 undiluted, using a paint roller or a brush, on dry surfaces, free from dust. When the surfaces are very porous and the product is quickly being absorbed, it is recommended to apply a second coat while the first coat is still wet. Remove any residues using a dry, soft, lint-free cloth. If a shiny finished surface is required,

# DUROSTICK D-22



## Water and oil repelling agent for marble & granite

it is recommended to apply the self-polishing liquid for marble, honed or textured granite and cotto flooring, DUROSTICK D-25.

### NOTE

After drying, the product is harmless to health and the environment.

### CLEANING

Clean all tools with THINNER 101 of DUROSTICK, immediately after use.

### CONSUMPTION

100-150ml/m<sup>2</sup> per coat.

### STORAGE

Store in shaded places, away from any heat source, for at least 24 months from production date.

### PACKAGING

Carton box with 15 pcs. of 1lt each one Carton box with 6 pcs. of 2.5lt each one

TECHNICAL SPECIFICATIONS	
Form - Color	Liquid - Transparent
Density	0.77±0.04kg/lt
Gloss	Matte
Application temperature	From +5°C to +35°C
Foot traffic	After 12 hours
Duration of watertightness	2 years (exterior waterproofing), 5 years (interior waterproofing)
Water absorption coefficient	W ≤0.5 kg/m <sup>2</sup> ·h

V.O.C. (Volatile Organic Compounds): Limit value of maximum content of V.O.C. per EU (Directive 2004/42/EC) for this product (class A/h: 'Binding primers', Type SB): 750gr/lt (2010). The ready to use product contains maximum 672gr/lt V.O.C.

### DUROSTICK S.A.

MANUFACTURING OF ADHESIVES, PAINTS & MORTARS  
 ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,  
 Tel: +30 211 60 03 500-599, +30 210 55 16 500, +30 210  
 55 98 350, Fax: +30 210 55 99 612  
 THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,  
 STREET, DA 10, GR: 570 22, Tel: +30 2310 795 797, +30  
 2310 797 365, Fax: +30 2310 797 367  
 E-mail: info@durostick.com

The technical specifications and directions of use contained in this technical brochure are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.