



DUROSTICK GROUT SCRAPER

PROPERTIES

Extremely durable grout scraper with an ergonomic soft-grip handle. The product is suitable and necessary for easy grout removal. It features two hard blades, with the ability to remove one for narrower (smaller) joints. The ease of use makes it an indispensable tool for the complete or the partial removal of cementitious grouts.

APPLICATIONS

DUROSTICK Grout Scraper quickly and easily removes worn out or dirty cementitious grouts. It then facilitates the grouts' renewal; cleanliness, watertightness, and even the re-grouting process with cementitious or epoxy grouts.

USE

- **Destroyed grout:** Remove the existing cementitious grout to a depth from 3mm to 5mm to make before regrouting. Redefine, if need be, the final color of the grout. Select

one of the three cementitious VITREOUS GROUTS (0-3mm, 1-10mm, 5-20mm) of DUROSTICK, the FLEXIBLE & OIL REPELLENT TILE & MARBLE GROUT 1-8mm, or the epoxy grout DUROPOXY that can be cleaned easily and quickly only with water.

- **Worn-out grout:** Remove the existing cementitious grout to a depth from 2mm to 3mm before regrouting, in the same way as described above.

- **Stained or discolored grout (usual floor grout occurrence):** Quickly and easily, without the use of strong or caustic chemicals, clean (scrape) the grout surface (to a depth of 0.5mm at the most), wipe away and remove all dust and dirt. Use a wet sponge and clean the residue. Allow for the cleaned surface to dry. Once dry, apply D-16 HYDROSTOP, the waterproofing agent for grout joints, available in a convenient container with a nozzle for easy application. In this way the grout is 'rejuvenated', it recovers its original color(s) and retains its watertightness for a long time.