

# ACID TILE CLEANER



For construction residues



## ■ PROPERTIES

Powerful acid cleaner for removing construction residues.

Dissolves and removes residues from excess grouts, tile adhesives and cements that were created during the installation stages. Thoroughly cleans and removes stains from oils, coffee, drinks, lime, emulsion paints, rust etc. With minimal scrubbing, it removes pollutants accumulated over time in the grout joints, making their colors more vibrant.

## ■ APPLICATIONS

DUROSTICK's ACID TILE CLEANER works within minutes on walls and floors lined with ceramic tiles or granite. Use the cleaner only after allowing at least for 20 days to pass from the grouting completion. It easily removes construction residues from tools.

## ■ LIMITATION OF USE

Not recommended for cleaning decorative tiles, marble, limestone and sanitary fixtures.

## ■ USE

### 1. Application preparation

Open doors and windows to prevent vapour accumulation. Protect eyes and hands using goggles and rubber gloves, respectively. Remove all stainless steel utensils from the application, and adjacent, areas. Protect all non-removable items, such as bathroom faucets, stainless steel sinks and anything else of similar materials, using plastic sheathing to cover everything up. This precautionary action will prevent oxidation of the materials from the vapours of the cleaner. It is highly advisable to test the product on a tile, before applying it to the surface (preventively). This is to avoid any possible corrosion or discoloration that very rarely occurs in exceptionally limited types of tiles.

### 2. Application

The tile cleaner is applied undiluted to the surface. Using a stiff broom or a scrubbing sponge, scrub for 2-3 minutes and rinse with water thoroughly. Follow

# ACID TILE CLEANER



## For construction residues

the same procedure to revitalize the color of stable and sound grouts.

### ■ CONSUMPTION

1lt/5-7m<sup>2</sup> of surface.

### ■ STORAGE

Store in shaded places protected from frost, for 36 months from production date.

### ■ SAFETY DIRECTIONS

The product is corrosive and an irritant to the respiratory system. Recommended to keep locked, away from the reach of children and apply in well ventilated areas.

Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

### ■ PACKAGING

Carton box with 15pcs of 1lt each one  
5lt, 20lt containers

TECHNICAL SPECIFICATIONS	
■ Form - Color	Liquid - Transparent
■ Density	1.05±0.05kg/lt
■ pH	0-1
■ Application temperature	From +5°C to +35°C
■ Scent	Lemon
■ Contains	Hydrochloric acid
■ Permit No. by General Chemical State Laboratory ELEFSIS 3093/2008	

### DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,  
PAINTS & MORTARS

**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,  
Tel: +30 211 60 03 500-599, +30 210 55 16 500,  
+30 210 55 98 350, Fax: +30 210 55 99 612

**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,  
STREET, DA 10, GR: 570 22,  
Tel: +30 2310 795 797, +30 2310 797 365,  
Fax: +30 2310 797 367  
Email: [info@durostick.com](mailto:info@durostick.com)

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.