

# D-22




---

## Water and oil repelling agent for marble & granite



### ■ PROPERTIES

Siloxane-based, waterproofing and oil repelling liquid with exceptional penetrating ability (micro technology). Its application creates an invisible surface film that does not peel off or yellow and does not slip. Its application prevents staining from oil, wine and soft drinks, ink, rust, as well as pet stains, air pollutants, etc.

### ■ ADVANTAGES

- Ready to use - easy application.
- Excellent water & oil repellency.
- Immediate effectiveness after the application.

### ■ APPLICATIONS

DUROSTICK's D-22 is applied on building facades made from marble and granite. Its application prevents the absorption of atmospheric pollutants

for at least 4 years and makes cleaning easier.

It is necessary for kitchen countertops and bathroom sinks, steps, as well as pebbles of various sizes and colors. It protects, over time, the historic and aesthetic value of statues and monuments. On lined walls and floors, it prevents salts and alkalis to rise to the surface and stain them. D-22 protects the surfaces from the absorption of stains within polished or honed marble on balconies or interior surfaces, after the watering of plants in pots.

### ■ USE

#### 1. Surface preparation

##### Polished surfaces

Before waterproofing the surface(s), it is recommended to test it, so as to verify that the surface can absorb the product. Prior to the waterproofing and to reach the best result possible,



## Water and oil repelling agent for marble & granite

clean the application surfaces using the biodegradable cleaner for polished marble and granite BIOCLEAN of DUROSTICK.

### • Unpolished surfaces

When working with unpolished or heavily stained marble, the use of DUROSTICK's D-21 cleaner for marble, is highly recommended.

### 2. Application

Apply D-22 undiluted, using a paint roller or a brush, on dry surfaces, free from dust. When the surfaces are very porous and the product is quickly being absorbed, it is recommended to apply a second coat while the first coat is still wet. Remove any residues using a dry, soft, lint-free cloth. If a shiny finished surface is required, it is recommended to apply the self-polishing liquid for marble, honed or textured granite and cotto flooring, D-25 of DUROSTICK.

### ■ CLEANING

Clean all tools with THINNER 101 of DUROSTICK, immediately after use.

### ■ CONSUMPTION

100-150ml/m<sup>2</sup> per coat.

### ■ STORAGE

Store in shaded places, away from any heat source, for 24 months from production date.

### ■ SAFETY DIRECTIONS

The product is classified as harmful.  
It is recommended to keep away from the reach of children and apply in well ventilated areas.  
Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

### ■ PACKAGING

Carton box with 15pcs of 1lt each one  
Carton box with 6pcs of 2.5lt each one.

### TECHNICAL SPECIFICATIONS

■ Form - Color	Liquid - Transparent
■ Density	0.77±0.04kg/lt
■ Gloss	Matte
■ Application temperature	From +5°C to +35°C
■ Foot traffic	After 12 hours
■ Duration of watertightness	2 years (exterior waterproofing), 5 years (interior waterproofing)
■ Water absorption coefficient	W ≤ 0.5 kg/m <sup>2</sup> ·h

### V.O.C. (Volatile Organic Compounds):

Limit value of maximum content of V.O.C. per EU (Directive 2004/42/CE) for this product (class A/h: 'Binding primers', Type SB): 750gr/lt (2010). The ready to use product contains maximum 749gr/lt V.O.C.

**DUROSTICK S.A.,**  
MANUFACTURING OF ADHESIVES,  
PAINTS & MORTARS  
**ATHENS:** ASPROPYRGOS, ATTICA, GR: 193 00,  
Tel: +30 211 60 03 500-599, +30 210 55 16 500,  
+30 210 55 98 350, Fax: +30 210 55 99 612  
**THESSALONIKI:** INDUSTRIAL PARK-SINDOS, S.B. 44,  
STREET, DA 10, GR: 570 22,  
Tel: +30 2310 795 797, +30 2310 797 365,  
Fax: +30 2310 797 367  
Email: [info@durostick.com](mailto:info@durostick.com)