

D-25



Self polishing liquid for marble, honed granite & cotto flooring



■ PROPERTIES

Self polishing liquid, based on wax and special polymers. It offers excellent luster and protection for existing or new marble, honed granite and cotto. Its application will also highlight the natural beauty and aesthetic value of any marble and granite. It creates a clear protective membrane, it is slip resistant, antistatic and it has a pleasant scent.

■ ADVANTAGES

- Ready to use - easy application.
- Dries quickly.
- Does not yellow over time.
- Maintains and refreshes surfaces.

■ APPLICATIONS

DUROSTICK's D-25 is highly recommended for existing marble flooring and mosaic, because it restores their lost luster and shine. Suitable for both interior and exterior spaces, as well as for building facades, monuments, statues etc.

■ USE

1. Surface preparation

Clean all dull, unpolished existing marble surfaces using DUROSTICK's D-21 cleaner. Rinse and dry the surfaces thoroughly and apply the waterproofing liquid, D-22 or NANO PROOF MARMO DS-275 of DUROSTICK. Allow for 24 hours to pass and protect the surfaces using the self-polishing liquid D-25, by applying the product, as directed.

D-25



Self polishing liquid for marble, honed granite & cotto flooring

2. Application

On a clean surface, apply it undiluted using a soft, lint-free cloth or soft sponge until the product dries completely. Once dry, buff the surface lightly using a soft, dry cloth to give extra shine to the surface. To maintain the luster, one bottle cap of D-25 in the mopping water is sufficient, even when combined with other detergents.

■ CONSUMPTION

1lt/8-12m², depending on the surface.

■ STORAGE

Store in shaded places protected from frost, for 36 months from production date.

■ SAFETY DIRECTIONS

The product needs no hazard labeling, based on current European and national legislation. However, it is recommended to keep away from the reach of children. If swallowed, seek medical advice and show the container or label.

■ PACKAGING

Carton box with 15pcs of 1lt each one
5lt container

TECHNICAL SPECIFICATIONS	
■ Form - Color	Liquid, White, becomes transparent when dry
■ Density	1.00±0.05kg/lt
■ pH	8-9
■ Application temperature	From +5°C to +35°C
■ Temperature resistance	From -30°C to +100°C
■ Drying time	1 hour
■ Foot traffic	After 3 hours

DUROSTICK S.A.,
MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS
ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612
THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367
Email: info@durostick.com