

D-29 SPOT FREE



Oil repelling and waterproofing impregnating agent for tile & granite



■ PROPERTIES

Siloxane-based, oil repellent and waterproofing liquid, with high penetrating ability (micro technology). Once dry, the product creates an invisible and protective surface film, which does not peel and does not slip, even when the surface gets wet (increases the slip resistance of surfaces). Prevents stains from oils, wine and soft drinks, ink, as well as the creation of pet stains. Stains from mud rain and atmospheric pollutants are easily removed from surfaces protected with D-29 SPOT FREE.

■ ADVANTAGES

- Ready to use - easy application.
- Excellent water & oil repellency.
- Immediate effectiveness after the application.

■ APPLICATIONS

D-29 SPOT FREE is the necessary waterproofing agent for absorbent and/or non-glazed tiles, matte and shiny granite, natural cotto. Use for interior and exterior applications.

Apply DUROSTICK's D-29 SPOT FREE on kitchen countertops made of marble or granite, to keep them stain free. When installing absorbent tiles, granite and cotto, it is recommended to use the product before grouting with dark color grouting materials. By so doing, the risk of the surface discoloration or staining, from the strong pigments of the grouting materials, is avoided and the cleaning process is facilitated at the same time.

■ USE

1. Surface preparation

Three weeks after completing the tile installation and the grout is thoroughly dry, clean all construction residues using DUROSTICK's ACID TILE CLEANER. When dealing with existing tiles, refresh and clean the surface using the biodegradable cleaner for polished marble and granite, BIOCLEAR of DUROSTICK.

2. Application

Apply DUROSTICK's D-29 SPOT FREE undiluted, using a paint roller or a brush, on dust free and dry

D-29 SPOT FREE



Oil repelling and waterproofing impregnating agent for tile & granite

surfaces. When dealing with an absorbent surface and the first coat is immediately absorbed, it is recommended to apply a second coat while the first one is still wet. The cleaning of any residues is achieved using a clean and soft lint-free cloth.

■ CLEANING

Clean all tools with DUROSTICK THINNER 101, immediately after use.

■ COVERAGE

100-150ml/m² per coat.

■ STORAGE

Store in shaded places away from any heat source, for 18 months from production date.

■ SAFETY DIRECTIONS

The product is classified as harmful. It is recommended to keep away from the reach of children and apply in well ventilated areas. Before use, refer to the cautions on the product packaging or the Safety Data Sheet.

■ PACKAGING

Carton box with 15pcs of 1lt each one
Carton box with 6pcs of 4lt each one

TECHNICAL SPECIFICATIONS	
■ Form - Color	Liquid - Transparent
■ Density	0.77±0.04kg/lt
■ Gloss	Matte
■ Application temperature	From +5°C to +35°C
■ Foot traffic	After 12 hours
■ Duration of watertightness	2 years (exterior waterproofing), 5 years (interior waterproofing)
■ Water absorption coefficient	W ≤ 0.5 kg/m ² vh

V.O.C. (Volatile Organic Compounds):

Limit value of maximum VOC content according to EU (Directive 2004/42/CE) for the particular product (class A/h «Binding primers», Type SB): 750gr/lt (2010). Ready to use product contains maximum 749gr/lt V.O.C.

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,
PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367

Email: info@durostick.com