

DS-230



Adhesive fiberglass joint tape with 2.5x2.5mm mesh opening for drywall, cement board and cracks on concrete and plaster



■ PROPERTIES - APPLICATIONS

Self-adhering alkali resistant fiberglass tape with mesh opening 2.5x2.5mm and weight of 55gr/m². Necessary for strengthening horizontal and vertical gypsum and cement board joints.

■ APPLICATIONS

Apply immediately after the first coat during taping, when using the joint compound for drywall D-67. Coat over the tape with a second and final coat. Its application ensures resilient joints and protects from capillary cracks or bursting. Ideal for spot strengthening concrete cracks as well as for at length applications of joints between floors and walls, before the application of cementitious waterproofing products.

■ PACKAGING

Carton box: 72 pcs (roll 5cm x 20m)
24 pcs (roll 5cm x 90m)

■ TECHNICAL SPECIFICATIONS

■ Form	Alkali resistant fiberglass mesh
■ Color	White

DUROSTICK S.A.,

MANUFACTURING OF ADHESIVES,

PAINTS & MORTARS

ATHENS: ASPROPYRGOS, ATTICA, GR: 193 00,
Tel: +30 211 60 03 500-599, +30 210 55 16 500,
+30 210 55 98 350, Fax: +30 210 55 99 612

THESSALONIKI: INDUSTRIAL PARK-SINDOS, S.B. 44,
STREET, DA 10, GR: 570 22,
Tel: +30 2310 795 797, +30 2310 797 365,
Fax: +30 2310 797 367

Email: info@durostick.com

The technical specifications and directions of use contained in this technical data sheet are the results of the knowledge and experience of the company's research and development department, as well as from the real-life applications of the product. The recommendations and suggestions regarding the use of the products are made without guarantee since the respective conditions during their application are beyond the control of the company. For this reason, it is the user's responsibility to make sure that the product is suitable for the intended application as well as the application conditions of the project.